

**NEUTRIK****NF2C-B/2**

Pair of professional `Phono Plug` (`RCA` - or `CINCH` - type) - marked red and black.

Including 2 x 2 strain reliefs for cable O.D. 3.0 mm to 7.3 mm. Additional strain relief for cable O.D. up to 8.0 mm available as accessory.

Features & Benefits

- Makes ground before signal contact and breaks signal before ground
- No more disturbing noise and broken speaker cones
- Precisely machined to our demanding quality standards
- Neutrik unique chuck type strain relief
- Gold plated contacts

Product

Connector Type	Profi
Gender	male

Electrical

Capacitance between contacts	≤ 7 pF
Contact resistance	>100G mΩ
Dielectric strength	1,5 kVdc
Insulation resistance	> 100 GΩ
Rated current per contact	16 A
Rated voltage	50 V

Mechanical

Cable O.D.	3.0 - 7.3 mm
Lifetime	> 2000 mating cycles
Wire size	2,5 mm ²
Wire size	14 AWG
Wiring	Solder contacts

Material

Contact plating	5 μm Au over 5 μm Ni
Contacts	Brass (CuZn39Pb3)
Insert	PBTP 20 % GR
Shell	Brass (CuZn39Pb3)
Strain relief	Polyacetal (POM)

Environmental

Flammability	UL 94 HB
Standard compliance	IEC 601-14
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

