

97 Lever Action Crimping Pliers, also for two-hand operation



97 52 03



97 52 04



97 52 06



97 52 09



97 52 10



- ▶ new generation of lever action crimping pliers
- ▶ for solder-free electrical connections
- ▶ the new lever transmission reduces the handforce up to 30% compared with regular crimping pliers
- ▶ repetitive, standard conforming high crimping quality due to precision dies and integral lock (self-releasing mechanism)
- ▶ these tools have been set precisely (calibrated) in the factory
- ▶ two-hand operation for easy crimping of large conductor diameters
- ▶ easy handling as a result of well balanced centre of gravity, angled head and ergonomically shaped handles
- ▶ all stressed parts are made of special steel, oil-hardened and tempered
- ▶ head burnished, non-slip plastic coated handles

KNIPEX special

With the new generation of Crimping Pliers even large conductor cross sections that normally require a high handforce can be crimped easily. The new lever transmission reduces the necessary handforce up to 30% compared with regular crimping pliers.



First step: move the handle with two fingers only until both jaws touch the connector to be crimped



Second step: now use the whole hand for further crimping procedure



Third step: when greater handforce is required, such as e. g. when crimping insulated connectors 6.0 mm², two hand operation is possible by the longer handles

Article-No.	EAN-Code	Range of Application	Capacity		Length		g
			mm ²	AWG	mm	g	
97 52 03	025443	non-insulated terminals and plug connectors	4.0 - 10.0	11 - 7	250	565	
97 52 13	048084		0.5 - 10.0	20 - 7	250	570	
97 52 23	052159		16 + 25	5 + 3	250		
97 52 04	025450	non-insulated, open plug-type connectors	0.1 - 2.5	27 - 13	250	565	
97 52 05	025467		0.5 - 6.0	20 - 10	250	570	
97 52 06	025474	insulated terminals and plug connectors	0.5 - 6.0	20 - 10	250	560	
97 52 08	025481		0.5 - 6.0	20-10	250	575	
97 52 09	025498	end sleeves (ferrules)	10/16/25	7/5/3	250	570	
97 52 19	052142		35 + 50	2 + 0	250	575	
97 52 10	023678	COAX-, BNC- and TNC- connectors, RG 58			250	575	
97 49 94	030997	locator for Art.-No. 97 52 04					20
97 49 95	031000	locator for Art.-No. 97 52 05					20