

Certification Record

CUSTOMER	CLASS	FILE
Legrand Deri Usine de Brochy Bacqueville en Caux 76730 France	5411-06 TRANSFORMERS-Power-	110227-0-000
Refer to Class Description for program details		

- Control transformers, open type, Class 130 C insulation, 1 phase, 50/60Hz, Primary 230-400V +/- 15V.

Models	Secondary	V	Power VA
423 01 (Fr)	444 01(It)	24	40
423 02(Fr)	444 02(It)	24	63
423 03(Fr)	444 03(It)	24	100
423 04(Fr)	444 04(It)	24	160
423 05(Fr)	444 05(It)	24	250
423 06(Fr)	444 06(It)	24	400
423 08(Fr)	444 08(It)	24	630
423 10(Fr)	444 10(It)	24	1000
423 11(Fr)	444 11(It)	24	1600
423 12(Fr)	444 12(It)	24	2500
423 21(Fr)	444 21(It)	48	40
423 22(Fr)	444 22(It)	48	63
423 23(Fr)	444 23(It)	48	100
423 24(Fr)	444 24(It)	48	160
423 25(Fr)	444 25(It)	48	250
423 26(Fr)	444 26(It)	48	400
423 28(Fr)	444 28(It)	48	630
423 30(Fr)	444 30(It)	48	1000
423 31(Fr)	444 31(It)	48	1600
423 32(Fr)	444 32(It)	48	2500
424 21(Fr)	445 21(It)	115	40
424 22(Fr)	445 22(It)	115	63
424 23(Fr)	445 23(It)	115	100
424 24(Fr)	445 24(It)	115	160
424 25(Fr)	445 25(It)	115	250
424 26(Fr)	445 26(It)	115	400
424 28(Fr)	445 28(It)	115	630
424 30(Fr)	445 30(It)	115	1000
424 31(Fr)	445 31(It)	115	1600
424 32(Fr)	445 32(It)	115	2500
424 33(Fr)	445 33(It)	115	4000
424 41(Fr)	445 41(It)	230	40
424 42(Fr)	445 42(It)	230	63
424 43(Fr)	445 43(It)	230	100
424 44(Fr)	445 44(It)	230	160

424 46(Fr)	445 46(It)	230	400
424 48(Fr)	445 48(It)	230	630
424 50(Fr)	445 50(It)	230	1000
424 51(Fr)	445 51(It)	230	1600
424 52(Fr)	445 52(It)	230	2500
424 53(Fr)	445 53(It)	230	4000

642101(Uk)		24	40
642102(Uk)		24	63
642103(Uk)		24	100
642104(Uk)		24	160
642105(Uk)		24	250
642106(Uk)		24	400
642108(Uk)		24	630
642110(Uk)		24	1000
642111(Uk)		24	1600
642112(Uk)		24	2500
642161(Uk)		115	40
642162(Uk)		115	63
642163(Uk)		115	100
642164(Uk)		115	160
642165(Uk)		115	250
642166(Uk)		115	400
642168(Uk)		115	630
642170(Uk)		115	1000
642171(Uk)		115	1600
642172(Uk)		115	2500
642173(Uk)		115	4000
642201(Uk)		230	40
642202(Uk)		230	63
642203(Uk)		230	100
642204(Uk)		230	160
642205(Uk)		230	250
642206(Uk)		230	400
642208(Uk)		230	630
642210(Uk)		230	1000
642211(Uk)		230	1600
642212(Uk)		230	2500
642213(Uk)		230	4000

Models with electrostatic screen between primary and secondary

424 61(Fr)	445 61(It)	230	40
424 62(Fr)	445 62(It)	230	63
424 63(Fr)	445 63(It)	230	100
424 64(Fr)	445 64(It)	230	160
424 65(Fr)	445 65(It)	230	250
424 66(Fr)	445 66(It)	230	400

424 68(Fr)	445 68(It)	230	630
424 70(Fr)	445 70(It)	230	1000
424 71(Fr)	445 71(It)	230	1600
424 72(Fr)	445 72(It)	230	2500
424 73(Fr)	445 73(It)	230	4000
642221(Uk)		230	40
642222(Uk)		230	63
642223(Uk)		230	100
642224(Uk)		230	160
642225(Uk)		230	250
642226(Uk)		230	400
642228(Uk)		230	630
642230(Uk)		230	1000
642231(Uk)		230	1600
642232(Uk)		230	2500
642233(Uk)		230	4000
642181(Uk)		115	40
642182(Uk)		115	63
642183(Uk)		115	100
642184(Uk)		115	160
642185(Uk)		115	250
642186(Uk)		115	400
642188(Uk)		115	630
642190(Uk)		115	1000
642191(Uk)		115	1600
642192(Uk)		115	2500
642193(Uk)		115	4000

/ec