





Art No. HD0009

# **Scart to HDMI Converter**

SCART signal interface is an Analog Signal Standard Interface of Europe. It includes Analog RGB, CVBS and AUDIO (L/R). This Converter is a unique device that converts an analog SCART signal to an HDMI signal. It improved compatibility at the most possibility and output signals as fixed HDMI format at a resolution of 1280x720.

This SCART to HDMI Converter offers solutions for noise, space and security concerns, data center control, information-distribution, conference-room presentation, school and corporate training environments.

## **Specification:**

Signal Inputs/Output	
Input DDC Signal	5 volts p-p (TTL)
Input Video signal	0.5-1.0 volts p-p
input Video	RGB, CVBS
Output Video	HDMI 720p
Connector	
HDMI Connector	Type A (19 pin) female
SCART Connector	SCART (21 pin) female
Mechanical	
Size (L-W-H)	102x100x30.5 mm
Weight (Net)	320g
Environmental	
Operating Temperature	0°C to +70°C
Operating Humidity	10% to 85 % RH (no condensation)
Storage Temperature	-10°C to 80°C
Storage Humidity	5% to 90 % RH (no condensation)
Power Requirement	
External Power Supply	5V DC@2A
Power Consumption	5 Watts (max.)











Art No. HD0009

## **Scart to HDMI Converter**

#### Feature:

This Converter has many features that enable it to perform in a superior manner. Among those features you will find:

- Easy to use: Install in seconds, no need for setting
- Supports RGB, CVBS and AUDIO (L/R) input
- Automatically detect RGB(50/60Hz), CVBS(NTSC/PAL)
- Upscale to HDMI 720p output

### **Package Contents:**

- 1 x Scart to HDMI Converter
- 1 x 5V DC Power Supply
- 1 x User Manual

## **Packaging Information:**

• Packing Dimension: 202x191x50mm

• Packing Weight: 0.56kg

Carton Dimension: 460x330x430 mm

Carton Q'ty: 20pcsCarton Weight: 12.2kg







