KÖNIG ELECTRONIC

Your World, Our Technology

Power Line IP Camera

Extra camera for SEC-CAMIP40

USPs:

- Plug & view
- Homeplug technology
- Video over existing power line
- Extendable to 16 cameras (with SEC-CAMIP40)
- Compatible with 3G-devices

General information:

The SEC-CAMIP40EC is an IP camera with an integrated homeplug, based on the homeplug technology. The video signal is delivered by the existing power line. By using the existing power line, the IP camera can be connected to each power outlet within the power network. No network cables required. The IP camera operates with P2P (Peer to Peer) technology. Just install the software and enter the present unique ID and password to connect to the IP camera. The live video can be viewed instantly via the network. A free website provides live view anywhere, any place without any IP setting or router configuration.

Specifications:

• Image sensor:	1/4.5" VGA sensor
• Resolution:	640x480, 320x240
• Display FPS:	Max. 30 fps
• Video compression:	MJPEG
• View angle (manual):	Pan 0°~350°, tilt 0°~135°
• IR distance (night vision)	Max. 5 m
• Power source:	100~240 V AC
• Homeplug:	1200 Mbps
• Dimensions:	205x123x123 mm
• Weight:	405 g (including base)
System requirements:	
• CPU:	Pentium® Dual-Core or later
• RAM:	1 GB or more
• Display:	1024x768/96 DPI
• OS:	Windows® XP/Vista/7
• Internet Explorer:	ActiveX needed (free download)
• Network:	Ethernet 100 base T or faster

Downloads:

Manual

Software

Sales information:

Order code:	**SEC-CAMIP40EC**
Description:	Power line IP camera
Packaging:	Giftbox
TARIC code:	8525801990

CE

5 412810 150526

	Quantity	LxWxH (mm)	Weight
Single	1 pc	275x260x105	960 g
Master	5 pcs	550x280x305	5.7 kg

©2011 König®. All rights reserved. König® is a registered trademark.
Specifications are subject to modification without prior notice. Contents may differ slightly from what is shown.
König can not be held responsible, nor liable for the information contained in this document.