



IP Switchable 8-Port PDU with Metering SNMP

Art no.: PDU8S01

Technical Features

Remote power management for individual sockets via TCP/IP and built-in 10/100 Ethernet port

Turn individual socket on/off or set schedule through the browser interface

Able to configure socket naming, set mail notification and check the power status & activity log

Supports SNMP management

Supports safe shutdown and surge protection

Flexible mounting on structured wiring enclosures, walls or behind tables and TV

Supports IP blacklist function effectively blocks malicious users

LCD Displays to view the operating status of ports and hosts

Included power cable IEC320-C19 to C20, 2 m













Technical Specifications

Input: 1x IEC320 C20 socket Connections Output: 8 x IEC320 C13 sockets

LAN: 3x RJ45 female port, 1 x RJ11 female

Rated Power AC 230 V/16 A, 50 Hz, max. 3600 W

10 A per port. Output Power

Total output: 16 A max.

State of the socket: LCD display Connection Indications

Power: LCD display

LAN (10/100 m): Orange/Green LED

Switches Reset, Restore to default and Power

0-50°C Operating Temperature

-20-60°C Storage Temperature

0-80% RH (non-condensing) Humidity

Housing Material Metal

44.2 x 15.9 x 4.45 cm **Dimensions**

Weight 2.42 kg Black Color

Package Contents

1x Power Distribution Unit

1x Power Cable

1x Mounting Kit

1x User Manual

Packaging Information

Packing Dimension 470 x 155 x 207 mm

2.8 kg Packing Weight

475 x 330 x 440 mm Carton Dimension

Carton Q'ty 4 pcs

12.2 kg Carton Weight



