

# LogiLink®

## Industrial Gigabit Ethernet Switch, 5-Port

Art. No.: NS202



Compact size 5-Port 10/100/1000 Base-TX Ethernet Switch, suitable for industrial application. Featuring 5 10/100/1000 Mbps auto-negotiation RJ45 ports, IP40-rated rugged aluminum case and a wide-ranging redundant power system (12–52 V DC). It is able to operate in any harsh environment with operating temperature ranging from -40 to 80°C.

### Features:

- » Industrial switch, 5-port, 10/100/1000Base-TX RJ45
- » Unmanaged, easy installation, plug-and-play
- » Compact and rugged metal housing, IP40
- » Free fall, shock and vibration stability
- » Power input: 12 to 52 V DC redundant power
- » Extended operation temperature: -40–80°C
- » Suitable for DIN-rail mounting



### Specification:

Protocols/Standards	IEEE 802.3, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, IEEE 802.3z
Interface	5 x 10/100/1000 Mbps RJ45 ports
Bandwidth	14 Gbps
Packet Buffer Memory	1,2 Mbit
Packet Forwarding Rate	10,5 Mpps
MAC Address Table	2K
Maximum Frame Size	9K bytes packet size
Flow Control	Back pressure for half duplex, IEEE 802.3x pause frame for full duplex
LED Indicator	Power: Red; Ethernet: Yellow
Network Cables	10Base-T: Cat.3/4/5 UTP (≤100 m); 100Base-Tx: Cat.5 or later UTP (≤100 m) 1000BASE-TX: Cat.6 or later UTP (≤100 m)
Power Input	12–52 V DC redundant power
Power Consumption	Max. 3 W
Surge Protection	±4 KV



NS202



Made in China



\*The specifications and pictures are subject to change without prior notice.  
\*All trade names referenced are the registered trademarks of their respective owners.

Best Connectivity

# LogiLink®

## Industrial Gigabit Ethernet Switch, 5-Port

Art. No.: NS202



Installation	DIN rail
Enclosure	IP40 aluminum housing
MTBF	>300.000 hours
Operating Temperature	-40–80°C
Storage Temperature	-40–80°C
Storage Humidity	5–95% RH non-condensing
Dimension	11,8 x 8,6 x 3,35 cm
Weight	0,36 kg



### Package Contents:

- » 1 x 5-Port Gigabit Ethernet Switch
- » 1 x User Manual

### Package Information:

- » Packing Dimension: 165 x 135 x 54 mm
- » Packing Weight: 0,41 kg
- » Carton Dimension: 445 x 350 x 343 mm
- » Carton Q'ty: 36 pcs
- » Carton Weight: 15,5 kg



\*The specifications and pictures are subject to change without prior notice.  
\*All trade names referenced are the registered trademarks of their respective owners.



NS202



Made in China

Best Connectivity