



2002-06-06

PRODUKTINFORMATION

Vi reserverar oss mot fel samt förbehåller oss rätten till ändringar utan föregående meddelande

ELFA artikelnr

54-106-26 Fläkt DC 3314 92x92

54-107-33 Fläkt DC 3312L 92x92

54-107-41 Fläkt DC 3312 92x92



- DC fans with electronically commutated external rotor motor. Fully integrated commutation electronics.
- With electronic protection against reverse polarity, blocking and overloading by PTC-resistor; partially impedance-protected.
- Fan of fibreglass reinforced plastic. PBTP housing, PA impeller.
- Air exhaust over struts. Rotational direction CW looking at rotor.
- Electrical connection via 2 leads AWG 22, TR 64. Stripped and tinned ends.
- Mass 190 g.

Series 3300

92 x 92 x 32 mm

Air flow		Nominal Voltage	Voltage Range	Noise		Sinter-Sleeve Bearings	Ball Bearings	Power Input	Nominal Speed	Temperature Range	Service Life L ₁₀		Curve	Type	Specials
m ³ /h	CFM	V DC	V DC	dB(A)	bels	□/■	Watt	min ⁻¹	°C	Hours	Hours	at t _{max}			
56	33.0	12	6...15	29	4.5	□	1.4	2 150	-20...+75	80 000/35 000	1		3312 GL		
56	33.0	12	6...15	29	4.5	■	1.4	2 150	-20...+75	80 000/35 000	1		3312 L		
68	40.0	12	6...15	34	4.8	□	1.7	2 600	-20...+75	70 000/30 000	2		3312 GM		
68	40.0	12	6...15	34	4.8	■	1.7	2 600	-20...+75	70 000/30 000	2		3312 M		
80	47.1	12	6...15	37	5.2	□	2.4	3 000	-20...+75	70 000/30 000	3		3312 G		
80	47.1	12	6...15	37	5.2	■	2.4	3 000	-20...+75	70 000/30 000	3		3312	58/62	
93	54.7	12	6...15	43	5.7	■	3.5	3 500	-20...+75	65 000/27 500	5		3312-177		
56	33.0	24	12...28	29	4.5	■	1.4	2 150	-20...+75	80 000/35 000	1		3314 L		
68	40.0	24	12...28	34	4.8	■	1.7	2 600	-20...+75	70 000/30 000	2		3314 M		
80	47.1	24	12...28	37	5.2	□	2.4	3 000	-20...+75	70 000/30 000	3		3314 G		
80	47.1	24	12...28	37	5.2	■	2.4	3 000	-20...+75	70 000/30 000	3		3314		
85	50.0	24	12...28	40	5.4	■	3.0	3 200	-20...+75	60 000/25 000	4		3314-140		
107	63.0	24	12...28	47	6.0	■	5.3	4 000	-20...+75	57 500/25 000	6		3314 H		
80	47.1	48	36...56	37	5.2	■	2.7	3 000	-20...+75	70 000/30 000	3		3318	58	
107	63.0	48	36...56	47	6.0	■	5.5	4 000	-20...+75	57 500/25 000	6		3318 H	60/62	

