


Data Sheet



Type Number 6016
Designation IEC CR 2016
System Li-Manganese dioxide / Organic Electrolyte

UL Recognition:..... MH 13654 (N)
Nominal Voltage 3 V
Typical Capacity C 90 mAh
 Load 15 kOhm, at 20°C down to 2 V

Weight (approx.) 1,8 g
Volume 0,5 ccm
Coding..... Date of Manufacturing Month/Year

Temperature Ranges

	min	max.
Storage	-55°C	70°C
Discharge	-20°C	65°C

Dimensions

	min	max.
Diameter (A)	19,7	20,0
Height (B)	1,4	1,6
Shoulder Diameter[E].....	18,4	
Shoulder Height [C].....	0,1	

Segment Electronic

Main Applications Watch
 Photo
 Electronic

Typical Capacities (at 20°C)

Discharge Type	Load	End Voltage:	2.0 V
Continuous	15000 Ω	Time:	450 h
24h/d, 7d/w		Capacity [mAh]:	90
Current [μA]:	200	Energy [mWh]:	270

All Data contained herein is for single cells

For battery applications, performance data may vary from single cell data, depending on specific battery configuration

VARTA Microbattery GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst
 Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553

Subject to change without prior notice!
 Date of issue: 2004-12-16