



USB 2.0 & FireWire 1394A PCI Combo Karte (VIA)

Merkmale USB 2.0:	• USB Version 1.1 bis 2.0 • Kompatibel zu Microsoft Windows Standard Open HCD Treiber, Unterstützt bis zu 127 Geräte • Unterstützt 32-Bit PCI-Bus und PCI-X Bus mit 5V oder 3.3V (33MHz)
Merkmale FireWire 1394A:	• FireWire 1394A (400) • Kompatibel IEEE 1394-1995, 1394a (rev. 1.1) und OHCI Interface Spezifikation 1.0 • PCI 32-Bit 33MHz Interface, Unterstützt bis zu 63 Geräte • Unterstützt „Hot-swapping“ somit können externe Geräte bei laufendem Betriebs des PC, rausgezogen und eingesteckt werden
Chip-Set :	• VIA VT6212L und VT6306
Datentransfer-Rate :	• USB 2.0: bis 480Mbps / FireWire 1394A: bis 400Mbps /
Anschlüsse :	• USB 2.0: 3 x Externe A-Buchsen und 1 x Interne A-Buchse • FireWire 1394A: 2 x 6 Pin Externe Buchse und 1 x 6 Pin Interne Buchse
Betriebssysteme :	• Windows 2000 / XP / Server 2003 / Vista
Hardwaresysteme :	• PCI- und PCI-X Bus
Abmessung / Gewicht :	• 120 x 30 mm / 150g
Lieferumfang :	• MX-12000, Handbuch



USB 2.0 & FireWire 1394A PCI combo card (VIA)

Feature USB 2.0:	• USB version 1.1 to 2.0 • Compatible to Microsoft Windows Standard Open HCD Driver, Support up to 127 device • Support 32-Bit PCI-Bus and PCI-X Bus with 5V and 3.3V (33MHz)
Feature FireWire 1394A:	• FireWire 1394A (400) • Compliant IEEE 1394-1995, 1394a (rev. 1.1) and OHCI Interface Specification 1.0 • PCI 32-Bit 33MHz Interface, Support up to 63 device • "Hot-wapping" features allow you to connect/disconnect devices without powering down your system
Chip-Set :	• VIA VT6212L und VT6306
Data transfer rate :	• USB 2.0: up to 480Mbps / FireWire 1394A: up to 400Mbps
Connectors :	• USB 2.0: 3 x external A-female and 1 x internal A-female connector • FireWire 1394A: 2 x 6 pin external female and 1 x 6 pin internal female connector
Operating system:	• Windows 2000 / XP / Server 2003/ Vista
Hardware system :	• PCI- and PCI-X Bus
Size / Weight :	• 120 x 30 mm / 150g
Packaging contents :	• MX-12000, Manual

Anwendung/Application :

