

You are here: Products » Heatsinks f.cool » Profile heatsinks and fluid coolers » Standard extruded heatsinks » SK 04 ... » SK 04

Heatsinks f.cool

- ▼ Profile heatsinks and fluid coolers
  - Standard extruded heatsinks
  - Extruded heatsinks for lock-in retaining spring
  - Extruded heatsinks for PCB mounting
  - Extruded heatsinks for DC/DC converter
  - Retaining springs for transistors
  - U-Extruded heatsinks
  - Die-cast heatsinks
  - Fin coolers
  - Fluid coolers
  - Aluminium flat-, quadrangular-, angled-, U- & T-profiles
- ▶ Heatsinks and active heatsinks for processors
- ▶ Finger-shaped heatsinks
- ▶ Cooling aggregates
- ▶ Accessories for electronic components
- ▶ Cases f.case
- ▶ Connectors f.con

Standard extruded heatsinks

SK 04 75 SA

97 x 25 mm, with guideway for cover plates or blanks

add to request



Features Technical Drawing Service

width	97 mm
height	25 mm
plate thickness	4 mm
lengths	100 mm
R <sub>max</sub>	1.3 - 2.8 K/W
drilling pattern	TO 3 CB SSR 1 SSR 2
surface	black anodised

surface