

2G/3G/4G LTE Multiband Bar Antenna

SmartBlade™ is an Omni-directional multi-band antenna with a slim and discreet design. It is designed to meet a constant need for improved and reliable communications such as M2M, vehicles and energy applications.

FEATURES

Easy installations with adhesive mount on glass or other nonconductive surface

BENEFITS

- 698 960 MHz/1420 -1520MHz/1710 - 2690 MHz
- Slim and flexible design made it suitable for curved surface mounting.

MARKETS

- Tracking devices
- Vehicle sectors
- Utilities and industrial control system, remote monitoring
- IoT

Other indoor and outdoor areas

1710-

2200-

SPECIFICATIONS

ELECTRICAL Frequency Band

Frequency Band [MHz]	98-780	790-960	1427- 1510	1710- 2170	2200- 2690
VSWR	< 2.2:1	< 2:1	<2:1	<2:1	< 2:1
Efficiency (%)	55%	68%	70%	70%	62%
3D Max Gain (dBi)	1.5	2.5	3	4.5	5.5
# port		1			
Impedance		50Ω			
Polarization		Linear			
Pattern Azimuth		Omni-directional			
Max power	10W (ambient temp. of 25°C)				
MECHANICAL Dimension (LxWxH)		114 x 24 x 4.4 (incl. 1.3mm 3M adhesive)			
Weight		~ 20g (incl. 20cm cable with SMA connector)			
Color		Grey, black			
Cable		RG316, standard or up request			
Connector		SMA(m) standard or upon request			
Material		Dryflex, FR4			
Installation	Adhesive mount on non-conductive surface				
Temperature (storage/operating)		-40°C~ +85°C			
IP Class		IP65			
RoHs compliant	Yes				

^{*}All RF data are performed on a 5mm thick glass with a 20cm long RG316 cable. Smarteq reserves the right to change specifications without prior notice.





