



MATERIALS

HOUSING: HI-TEMP PLASTIC(UL 94V-0),
 SHELL: SPCC, NICKEL PLATED
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATED ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 1 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -25°C~+85°C

MINI USB 5P/M FRONT SHELL

MINI USB 5P/M BACK SHELL

MINI USB 5P/M HOUSING FRONT 5 BACK 5

APPD. 核准 HELEN DWG. 製圖 ABBY DATE 制表日 2015/04/30		RoHS Compliant HSM 玄茂科技股份有限公司 HSIUAN MAO TECHNOLOGY CO., LTD.		PART NAME 品名 MINI USB B MALE 5P ASSEMBLY TYPE (5P TO 5P) NICKEL SHELL SELECTIVE GOLD PLATING BLACK INSULATOR ROHS	
SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1		GENERAL TOLERANCE: .X ±0.30 Ang. ±3° .XX ±0.20 .XXX ±0.10 SIZE: 紙張尺寸 A4 REV. 版次 A		PART NO. 料號 C8320-05BMASB2R	