Report Date : 16/06/2011

REVISION DATE NOVEMBER 2010



SAFETY DATA SHEET BLOC' LUBE GREEN

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME BLOC' LUBE GREEN

PRODUCT NO. BLV

EBLV15ML

ZΕ

APPLICATION Tamper evident seal

SUPPLIER ELECTROLUBE. A division of

HK WENTWORTH LTD ASHBY PARK, COALFIELD

WAY,

ASHBY DE LA ZOUCH, LEICESTERSHIRE LE65 1JF

UNITED KINGDOM +44 (0)1530 419600 +44 (0)1530 416640 info@hkw.co.uk

EMERGENCY TELEPHONE +44 (0)1530 419600 between 8.30am - 5.00pm Mon – Fri

2 HAZARDS IDENTIFICATION

Highly flammable.

Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

Irritating to eyes.

CLASSIFICATION (1999/45) Xi;R36. F;R11. R66, R67.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
BUTYL ACETATE -norm	204-658-1	123-86-4	30-60%	R10 R66 R67
ETHYL ACETATE	205-500-4	141-78-6	10-30%	F;R11 Xi;R36 R66 R67
PROPAN-2-OL	200-661-7	67-63-0	10-30%	Xi;R36. F;R11. R67.

The Full Text for all R-Phrases is Displayed in Section 16

COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels

4 FIRST-AID MEASURES

NOTES TO THE PHYSICIAN

Treat symptomatically

INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

DO NOT INDUCE VOMITING! Provide fresh air, warmth and rest, preferably in comfortable upright sitting position. Rinse mouth thoroughly. Get medical attention.

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

Report Date: 16/06/2011

REVISION DATE NOVEMBER 2010

BLOC' LUBE GREEN

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Alcohol resistant foam. Powder. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES

Move container from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Wear necessary protective equipment.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	STD	TWA - 8 Hrs		STEL	Notes	
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m3	200 ppm	966 mg/m3	
ETHYL ACETATE	WEL	200 ppm		400 ppm		
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT





ENGINEERING MEASURES

Provide sufficient ventilation during operations which cause vapour formation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

HAND PROTECTION

Use protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear approved safety goggles.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke.

Report Date: 16/06/2011

REVISION DATE NOVEMBER 2010

BLOC' LUBE GREEN

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Liquid **COLOUR** Green

ODOUR Characteristic

SOLUBILITY Immiscible with water VISCOSITY

850 - 1450 mPas @ 20 °c

(68

F)

FLASH POINT (°C) 3.3 (37.94 F) CC (Closed

cup).

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

11 TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION

No information available.

INHALATION

May cause irritation to the respiratory system.

INGESTION

May cause stomach pain or vomiting.

SKIN CONTACT

Product has a defatting effect on skin. Prolonged or repeated exposure may cause severe irritation.

EYE CONTACT

Irritating to eyes.

Name **ETHYL ACETATE** Toxic Dose 1 - LD 50 5620 mg/kg (oral rat) Toxic Dose 2 - LD 50 18,000 mg/kg (oral-rbt) Toxic Conc. - LC 50 1600 ppm/4h (inh-rat) Name **BUTYL ACETATE -norm**

Toxic Dose 1 - LD 50 14,100 mg/kg (oral rat)

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment.

Name ETHYL ACETATE

LC 50, 96 Hrs, Fish mg/l 270 EC 50, 48 Hrs, Daphnia, mg/l 2306

BUTYL ACETATE -norm Name

LC 50, 96 Hrs, Fish mg/l >96 EC 50, 48 Hrs, Daphnia, mg/l 72.8 IC 50, 72 Hrs, Algae, mg/l 674

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

GENERAL

For US Domestic transportation this product is classified as a Consumer Commodity. For International transportation this product is classified as UN1263 PAINT

Report Date: 16/06/2011

REVISION DATE NOVEMBER 2010

BLOC' LUBE GREEN



PROPER SHIPPING NAME PAINT

PROPER SHIPPING NAME CONSUMER COMMODITY

ENVIRONMENTALLY No.

HAZARDOUS

SUBSTANCE/MARINE

POLLUTANT

UN NO. ROAD 1263 ADR CLASS NO. 3

ADR CLASS Class 3: Flammable liquids.

ADR PACK GROUP

HAZARD No. (ADR)

33

ADR LABEL NO.

HAZCHEM CODE

•3YE

UN NO. SEA

IMDG CLASS

IMDG PACK GR.

II

 EMS
 F-E, S-E

 UN NO. AIR
 1263

 AIR CLASS
 3

 AIR PACK GR.
 II

15 REGULATORY INFORMATION

LABELLING







Highly Flammable

RISK PHRASES

R11 Highly flammable.
R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S16 Keep away from sources of ignition - No smoking.

S25 Avoid contact with eyes. S37 Wear suitable gloves.

Use only in well-ventilated areas.

UK REGULATORY REFERENCES

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

Chemicals (Hazard Information & Packaging) Regulations.

ENVIRONMENTAL LISTING

Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980. Control of Pollution Act 1974.

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC.

Dangerous Substance Directive 67/548/EEC.

Dangerous Preparations Directive 1999/45/EC.

Report Date : 16/06/2011

REVISION DATE NOVEMBER 2010

BLOC' LUBE GREEN

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

REVISION COMMENTS

Revised in accordance with CHIP3 and EU Directives 1999/45/EC and 2001/58/EC

ISSUED BY

Helen O'Reilly

REVISION DATE NOVEMBER 2010

REV. NO./REPL. SDS 5

GENERATED

SDS NO. 10800

RISK PHRASES IN FULL

R10 Flammable.
R11 Highly flammable.
R36 Irritating to eyes.

Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.