


IR-Empfänger/Demodulator-Baustein

IR-Receiver/Demodulator Device

SFH 506



Maße in mm, wenn nicht anders angegeben/Dimensions in mm, unless otherwise specified.

Wesentliche Merkmale

- Fotodiode mit integriertem Verstärker
 - Angepaßt an verschiedene Trägerfrequenzen
 - Gehäuse schwarz eingefärbt: Verguß optimiert für eine Wellenlänge von 950 nm
 - Hohe Störsicherheit
 - Geringe Stromaufnahme
 - 5 V Betriebsspannung
 - Hohe Empfindlichkeit
 - TTL und CMOS kompatibel
 - Verwendbar bis zu einem Tastverhältnis $\leq 40\%$

Anwendungen

- #### ● Empfänger für IR-Fernsteuerungen


Features

- Photodiode with hybride integrated circuit
 - Available for several carrier frequencies
 - Black epoxy resin, daylight filter optimized for 950 nm
 - High immunity against ambient light
 - Low power consumption
 - 5 V supply voltage
 - High sensitivity (internal shield case)
 - TTL and CMOS compatibility
 - Continuous transmission possible ($t_{\text{pri}}/T \leq 0.4$)

Applications

- IR-remote control preamplifier modules

Typ	Trägerfrequ.	Bestellnr.	Typ	Trägerfrequ.	Bestellnr.
Type	Carrier Frequency kHz	Ordering Code	Type	Carrier Frequency kHz	Ordering Code
SFH 506-30	30	Q62702-P1196	SFH 506-38	38	Q62702-P1199
SFH 506-33	33	Q62702-P1197	SFH 506-40	40	Q62702-P1200
SFH 506-36	36	Q62702-P1198	SFH 506-56	56	Q62702-P1201

**Blockschaltbild****Block Diagram**

Grenzwerte Maximum Ratings


Bezeichnung Description	Symbol Symbol	Wert Value	Einheit Unit
Betriebs- und Lagertemperatur Operation and storage temperature range	T_A, T_{stg}	- 25 ... + 85	°C
Sperrschichttemperatur Junction temperature range	T_j	100	°C
Löttemperatur Lötstelle 2 mm vom Gehäuse; Lötzeit $t \leq 5$ s Soldering temperature soldering joint ≥ 2 mm distance from package, soldering time $t \leq 5$ s	T_s	260	°C
Betriebsspannung Supply voltage	Pin 2 V_s	- 0.3 ... + 6.0	V
Betriebsstrom Supply current	Pin 2 I_{cc}	5	mA
Ausgangsspannung Output voltage	Pin 3 V_{out}	- 0.3 ... + 6.0	V
Ausgangsstrom Output current	Pin 3 I_{out}	5	mA
Verlustleistung Total power dissipation $T_A \leq 85$ °C	P_{tot}	50	mW

Kennwerte ($T_A = 25^\circ\text{C}$)

Characteristics

Bezeichnung Description	Symbol Symbol	Wert Value	Einheit Unit
Betriebsspannung Supply voltage	V_s	typ. 5.0 (4.5 ... 5.5)	V
Bestrahlungsstärke (Testsignal, s. Figure 2) Threshold irradiance (test signal, see Fig. 2)	$E_e \text{ min}_{(30-40 \text{ kHz})}^{1)}$ $E_e \text{ min}_{(56 \text{ kHz})}^{1)}$ $E_e \text{ max}^{1)}$	typ. 0.35 (< 0.5) typ. 0.4 (< 0.6) 30	mW/m^2 W/m^2
Wellenlänge der max. Fotoempfindlichkeit Wavelength of max. sensitivity	$\lambda_{s \text{ max}}$	950	nm
Spektraler Bereich der Fotoempfindlichkeit Range of spectral sensitivity $S = 10\% \text{ of } S_{\text{max}}$	$\Delta\lambda$	830 ... 1100	nm
Halbwinkel Half angle	ϕ	± 45	deg.
Stromaufnahme Current consumption $V_s = 5 \text{ V}, E_v = 0$ $V_s = 5 \text{ V}, E_v = 40 \text{ 000 lx, sunlight}$	Pin 2 I_{CC} I_{CC}	0.6 (< 0.8) 1.0	mA mA
Ausgangsspannung Output voltage $I_{\text{OUT}} = 0.5 \text{ mA}, E_e = 0.7 \text{ mW/m}^2, f = f_0, T_p/T = 0.4$	Pin 3 $V_{\text{OUT low}}$	< 250	mV

¹⁾ In Verbindung mit einer typ. SFH 415 bei Betrieb mit $I_F = 0.5 \text{ A}$ wird eine Reichweite von ca. 35 m erreicht.¹⁾ Together with an IRED SFH 415 under operation conditions of $I_F = 0.5 \text{ A}$ a distance of 35 m is possible.



OHF02197

*) only necessary to suppress power supply disturbances

Figure 1 Externe Beschaltung
External circuit





Figure 2 Testsignal
Test signal


Relative sensitivity

$$E_{e \min}/E_e = f(f/f_0)$$




Sensitivity vs. dark ambient $T_p \text{ out} = f(E_e)$

$\lambda = 950 \text{ nm}$, optical test signal




Sensitivity vs. supply voltage disturbances, $E_{e \min} = f(\Delta V_s \text{ RMS})$

$E_{e \min} = f(\Delta V_s \text{ RMS})$




Sensitivity vs. electric field disturbance

$E_{e \min} = f(E)$, field strength of disturbance, $f = f_0$




Sensitivity vs. duty cycle

$$E_{e \min} = f(t_p/T)$$




Relative luminous intensity

$$S_{\text{rel}} = f(\lambda), T_A = 25^\circ\text{C}$$




Sensitivity vs. bright ambient


$E_{e \min} = f(E)$, $\lambda = 950 \text{ nm}$, ambient



Vertical directivity ϕ_y



Horizontal directivity ϕ_x



Output pulse $T_{on}, T_{off} = f(E_e)$ 