



DB 25P MALE

DB 25P FEMALE

- 1 _____
- 2 _____
- 3 _____
- 4 _____
- 5 _____
- 6 _____
- 7 _____
- 8 _____
- 9 _____
- 10 _____
- 11 _____
- 12 _____

- 13 _____
- 14 _____
- 15 _____
- 16 _____
- 17 _____
- 18 _____
- 19 _____
- 20 _____
- 21 _____
- 22 _____
- 23 _____
- 24 _____
- 25 _____

SHELL _____ SHELL

Product Number	CU.P/NO	Length+/- (mm)	Packing
301-16-448	RND 765-00033	1800+/-10mm	1pc/poly bag with single color printed RND Connect logo+ RND Label
301-16-449	RND 765-00034	3000+/-30mm	
301-16-450	RND 765-00035	5000+/-50mm	
301-16-451	RND 765-00036	10000+/-50mm	

NOTES:
 ELECTRICAL CHARACTER:
 1.100% OPEN&SHORTTESTING.
 2.ROHS and REACH COMPLIANT.
 3. Copper OD Toleranle +/- 0.02mm
 4.connector connection method: soldering.
 5.THIS PRODUCT INCLUDED THE RAW MATERIAL:
 PVC - COPPER WIRE - Gold-plated copper
 - nickel-plated copper - nickel plated Iron
 shell - PBT - solder wire

Temperature Range: 10°C . .60°C

C	CONNECTOR 2	DB 25P MALE NICKEL-PLATED	
B	CONNECTOR 1	DB 25P FEMALE NICKEL-PLATED	
A	CABLE	25C+1 28AWG(7X0.12BC) +D7X0.12BC +AL/MYLAR_OD7.0MM_color:BEIGE	
NO	ITEM	DESCRIPTION	