

Top View of Assembly

77.00 [3.031] В 147.00 [5.787]


SECTION A-A End View of Assembly




1554K



SECTION B-B Side View of Assembly



Top View Looking Inside Box



Lid

Available 16 Gauge Steel

Maximum P.C. Board Size

							Plate					
								NOTE: Hole	patterns same	•		
					1			as seen in to	p view of box.			
	-	160.00		15.00 🕳	-					I		1
		[6.299]		[.591]		_	130.66	38.71		-	_ 152.00	43.00
	(#8G		284	-	י ר		[5.144]	[1.524]			[5.984]	[1.693]
Î					A	•	.	\$	A	 	◆ R7.00 —	
			81.00 [3.189]			11.05		7		R2.00	[.276]	
90.00		454.00	[0.100]		77.47	÷ [.435]	Ø3.73 _	+	78.00	♦ [.079]		+
[3.543]		151.00 [5.945]			[3.050]				[3.071]		Ø3.80 –	¬ ,
1		[5.945]	• (\psi /	 	÷ [.147]	* (*	 	ф [.150]	*
					J /	A					_ 133.00	
					R8.33/	4	147.32		2 50		[5.236]	10.50
					[.328]		[5.800]		[.098]			[.413]
					[.328]	•			2.50 — — [.098]		[0.200]	

Purchased assembly includes box, lid and 4 cover screws. cover screws should be torqued to 2.5 lbf-in (30 cN-m) Polycarbonate version is 6508 approved inclosure Type 4X, 4, 12 File# E65324

	1554K								
	1554K Regular Enclosure								
	General Purpose ABS	1554KGY							
	Polycarbonate	1554K2GY							
	1554K Clear Lid Enclosure								
	Polycarbonate	1554K2GYCL							
	ACCESSORIES								
3]	Heavy Duty 16 Gauge Galvanized Steel Panels	1554JPL							
	Steel Panel / P.C. Board Machine Screw	1591MM100							
	[M3 X 8mm Nickel Plated]								
-	Steel Panel / P.C. Board Self Tapping Screw	1598ATS100							
L	[#6 X 1/4" (6.4mm) Nickel Plated]								
	Cover Screws (Pkg 4)	SC1554							
	[M4 X 20mm Stainless Steel]								



www.hammondmfg.com