

# EC Safety Data Sheet according to Directive 1907/2006

Trade name: Solder-wire H10; S-Sn60Pb40

Date of issue: 06.05.2003

Revised on: 01.07.2008

Date of print: 07.01.2009

Page: 1(4)

## 1. Name of product, characterization and company name

### Information on the product

Trade name: Solder-wire HS10 2510 S-Sn60Pb40

Usage of the product / preparation Solder wire for soft soldering

### Identification of the manufacturer / supplier

Address: Stannol GmbH  
Oskarstr. 3 -7  
42283 Wuppertal  
Phone: 0202 585 0  
Fax: 0202 585 155  
Emergency call: 0202 585 119  
E-mail: werner.kruppa@stannol.de

## 2. Possible hazards:

Not a composition for the purposes of the Dangerous Substances Regulations, but nevertheless observe items 4-16

## 3. Composition/Information on the components

Chemical characterization: Tin/Lead – alloy with flux max.3,5 % (halide activated)

### Composition according to EC 1907/2006:

Contents	CAS No.	EINECS No.	Symbols	R-phrases:	Substance
<60%	7440-31-5	231-141-8			Tin
Remainder	7439-92-1	231-131-3			Lead
<3,5%	8050-09-7	232-475-7	Xi	43	Rosin

The wording of the R-phrases stated is indicated in Section 16

## 4. First Aid measures

### General information:

If casualty is unconscious but breathing, place in the recovery position. If breathing has stopped apply artificial resuscitation or give oxygen by mask

### After inhalation:

Remove patient to fresh air. If irritation persists, obtain medical attention.

### After skin contact:

If any skin irritation develops seek medical attention

### After eye contact:

Flush **immediately** with plenty of water. In cases where spitting flux has entered the eye seek medical attention.

### After ingestion:

Rinse mouth immediately and drink plenty of water. Seek medical advice.

### Hints for doctors.

Inhalation of the flux fumes given off at soldering temperatures will irritate the nose, throat and respiratory system. Repeated or prolonged exposure to flux fumes may cause shortness of breath and cough..

### Physician's information

#### Treatment:

Decontamination, treatment of symptoms.

## 5. Fire fighting measures

**Suitable extinguishing media:** Use extinguishing media appropriate to surrounding fire conditions

**Special protective equipment for fire fighting** Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

## 6. Accidental release measures

Pick up and place in appropriate container

## 7. Handling and storage

The fumes produced during soldering should be extracted away from the breathing zone of the operators. Ensure the area is well ventilated. Wash hands with soap and warm water after handling, particularly before eating, drinking or smoking.

The product should be stored in a cool, dry area.

# EC Safety Data Sheet according to Directive 1907/2006

Trade name: Solder-wire H10; S-Sn60Pb40

Date of issue: 06.05.2003

Revised on: 01.07.2008

Date of print: 07.01.2009

Page: 2(4)

## 8. Exposure controls and personal protection

### Additional information on system design:

Local exhaust or dilution ventilation and control of process conditions are suitable methods..

### Substances with limit values to be monitored at the working place:

#### Danger to health at the working place:

Peak limit category:

### Working place limit values according to TRGS 900 from Section 2 for Germany:

Product name	CAS No.	ml/m <sup>3</sup> (ppm)	mg/m <sup>3</sup>	Type	Category	Remarks
Tin	7440-31-5		2	MAK (NL)		
Lead	7439-92-1		0,1	MAK (TLV)		

**BAT-Value** Lead/blood level: 700µg/l,  
Women below 45 years: 300µg/l

**Skin resorption / Sensitization:** Skin resorption ---- Sensitization: ----

### General protection and hygiene measures

Avoid direct contact with eyes, the skin and clothing.

### Personal protection

**Respiratory protection:** If concentrations are over the exposure limit, use a supplied air respirator.

**Hand protection:** Use heat resistant gloves if required.

**Eye protection:** Operators should wear goggles

**Personal protection:** Light protective clothing

## 9. Physical and chemical properties

**Form:** Form: Tin-Lead Solder  
Colour:silver

**Melting Point:** 183 °C

**Vapour Pressure:** n.a.

**Density(20°C):** 7-8 g/cm<sup>3</sup>

221 °C  
n.a.

## 10. Stability and reactivity

**Reaction with substances:** Possible with oxidising agents.

**Hazardous combustion or decomposition products:** Lead-oxides possible

## 11. Toxicological information

The toxicological classification of the product is based on the results of the calculation procedure of the general preparation directive 1999/45/EC.

### Acute Effects:

Acute intoxication by ingestion of skin contact with lead is improbable. High doses nevertheless lead to symptoms of poisoning. Inhalation of fumes can irritate the respiratory tract and eyes..

### Contamination through skin contact and inhalation:

All following items refer to pure lead

### Acute Toxicity

Type	Value in mg/Kg	Form	Species
LD.LO	160	oral	pigeon
LD.LO	1000	ip	rat

LD.LO (oral, pigeon): 160 mg/kg; TD.LO (oral, woman): 450 mg/kg (damage to nervous system); LD.LO (ip., Rat): 1000 mg/kg; TC.LO (inhal., human): 10 mg/m<sup>3</sup> ;

## 12. Ecological information

**General information:** Lead and combinations of lead are not biological reducible.

## EC Safety Data Sheet according to Directive 1907/2006

Trade name: Solder-wire H10; S-Sn60Pb40

Date of issue: 06.05.2003

Revised on: 01.07.2008

Date of print: 07.01.2009

Page: 3(4)

### 13. Disposal considerations

**Disposal information**

**Product:**

Contact a licensed professional waste disposal service to dispose of this material.

**Further information:**

Observe all federal, state and local environmental regulations. Collect metal for recycling

**Waste identity number:**

Waste identity number EAK-code: 120104

### 14. Transport information

**GGVS/ADR/RID:**

The product is not classified as hazardous for transport

### 15. Legal regulations:

**Labelling information:**

**The product is classified and labelled according to the EC Directives.**

**Water hazard class:**

Not subject to current legislation

**Classification according to the TA Luft:**

WGK 1 (weakly water-endangering)

**Ingredients:**

Organic materials class III; whole-carbon-concentration: Max. acceptable

Emission 50 mg/m<sup>3</sup> (mass-flow-rate  $\geq$  0,5 kg/h)

Tin, Lead, rosin

### 16. Further information

**R-phrases point 3: 43 May cause sensitization by skin contact**

**German regulations:**

See TRGS 505 "Lead and leaded dangerous compounds"

This statement is based on our current knowledge and offers no assurance of product properties.

**Department issuing the data sheet**

Stannol GmbH/Quality Assurance/Laboratory

**Contact person**

Dr. Kruppa