

Productname :	EMV 35	Creationdate :	09.11.11 Version : 1.0
Ref.Nr.:	BDS000771_3_20111109	Replaces:	AB27750

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

EMV 35
Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Conduction electric/thermal

1.3. Details of the supplier of the safety data sheet

CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele
Belgium
Tel.: +32(0)52/45.60.11
Fax.: +32(0)52/45.00.34
E-mail : hse@crcind.com

Subsidiaries		Tel	Fax
CRC Industries Finland Oy	Asemanrinne 13, 08500 Lohja	+358/(19)32.921	+358/(19)383.676
CRC Industries France	6, avenue du marais, B.P. 90028, 95102 Argenteuil Cedex	01.34.11.20.00	01.34.11.09.96
CRC Industries Deutschland GmbH	Südring 9, D-76473 Iffezheim	(07229) 303.0	(07229)30 32 66
CRC INDUSTRIES IBERIA S.L.U.	GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTRI. DE HONTORIA, 40195 SEGOVIA	0034/921.427.546	0034/921.436.270
CRC Industries Sweden	Kryptogatan 14, 431 53 Mölndal	0046/31 706 84 80	0046/31 27 39 91

1.4. Emergency telephone number

CRC Industries Europe, Belgium: Tel.: +32(0)52/45.60.11 (office hours)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to 67/548/EEC or 1999/45/EC:**

Health: R36: Irritating to eyes.



CRC Industries Europe bvba



Touwslagerstraat 1, 9240 Zele – Belgium
Tel (+32) (0) 52 / 45 60 11 – Fax (+32) (0) 52 / 45 00 34 – www.crcind.com

1 / 10

Productname :	EMV 35	Creationdate :	09.11.11 Version : 1.0
Ref.Nr.:	BDS000771_3_20111109	Replaces:	AB27750

	R66: Repeated exposure may cause skin dryness or cracking. R67: Vapours may cause drowsiness and dizziness.
Physical:	EXTREMELY FLAMMABLE
Environment:	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Warning symbol(s) :	EXTREMELY FLAMMABLE  Xi : IRRITANT 
Risk-phrase(s) :	R36: Irritating to eyes. R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R66: Repeated exposure may cause skin dryness or cracking. R67: Vapours may cause drowsiness and dizziness.
Safety-phrase(s) :	S2: Keep out of the reach of children. S16: Keep away from sources of ignition - No smoking. S23: Do not breathe vapours/spray. S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S35: This material and its container must be disposed of in a safe way. S51: Use only in well-ventilated areas.
Extra label elements according to Aerosol Dispenser Directive 75/324/EC:	Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Without adequate ventilation formation of explosive mixtures may be possible.

2.3. Other hazards

None

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Productname : EMV 35

Creationdate :

09.11.11 Version :

Ref.Nr.: BDS000771_3_20111109

Replaces:

1.0

AB27750

Hazardous ingredient	CAS-nr.	EC-nr	w/w %	symbol	R-phrases*	Notes
dimethyl ether	115-10-6	204-065-8	25-50	F+	12	A
n-butyl acetate	123-86-4	204-658-1	10-25		10-66-67	
Copper	7440-50-8	231-159-6	<20	Xn	22-36/37/38-52/53	B
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	203-539-1	5-10		10-67	A
propyl acetate	109-60-4	203-686-1 [1]	5-10	F,Xi	11-36-66-67	B
isopentyl acetate	123-92-2	204-662-3	1-5		10-66	A
butanone; ethyl methyl ketone	78-93-3	201-159-0	1-5	F,Xi	11-36-66-67	A
1H-Imidazole-1-ethanol, 2-(8-heptadecenyl)-4,5-dihydro-	95-38-5	202-414-9	<2.5	C,N	22-34-50/53	

Explanation notes

A : substance with Community workplace exposure limit

B : substance with national established workplace exposure limit

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
dimethyl ether		115-10-6	204-065-8	25-50	Flam. Gas 1, Press. Gas	H220	A
n-butyl acetate		123-86-4	204-658-1	10-25	Flam. Liq. 3, STOT SE 3	H226, H336	
propyl acetate		109-60-4	203-686-1 [1]	5-10	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225, H319, H336	B
isopentyl acetate		123-92-2	204-662-3	1-5	Flam. Liq. 3	H226	A
butanone; ethyl methyl ketone		78-93-3	201-159-0	1-5	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225, H319, H336	A

Explanation notes

A : substance with Community workplace exposure limit

B : substance with national established workplace exposure limit

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures**4.1. Description of first aid measures**

Contact with eyes :	If substance has got into eyes, immediately wash out with water for at least 15 minutes Seek medical advice
Contact with skin :	Remove contaminated clothing immediately and drench affected skin with plenty of water. Then wash with soap and water Seek medical attention if irritation persists
Inhalation :	Remove patient to fresh air Keep warm and at rest, in a half upright position. Loosen clothing Seek medical attention if ill effects occur
Ingestion :	Ingestion is unlikely to occur If swallowed accidentally, do not induce vomiting and seek medical advice.

Productname :	EMV 35	Creationdate :	09.11.11 Version : 1.0
Ref.Nr.:	BDS000771_3_20111109	Replaces:	AB27750

4.2. Most important symptoms and effects, both acute and delayed

Inhalation :	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	May cause gastrointestinal disturbances Symptoms : sore throat, abdominal pain, nausea, vomiting
Skin contact :	May cause irritation. Symptoms : redness and pain
Eye contact :	Irritating to eyes Symptoms : redness and pain

4.3. Indication of any immediate medical attention and special treatment needed

General Advice :	If you feel unwell, seek medical advice (show the label where possible) If symptoms persist always call a doctor
-------------------------	---------------------------------------------------------------------------------------------------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C
Forms hazardous decomposition products
CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water
In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources
Ensure adequate ventilation
Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities



Productname :	EMV 35	Creationdate :	09.11.11 Version : 1.0
Ref.Nr.:	BDS000771_3_20111109	Replaces:	AB27750

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material
Place in appropriate container

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition
Take precautionary measures against static discharges
Equipment should be earthed
Use explosion-proof electrical/ventilating/lighting/?/equipment.
Use only non-sparking tools.
Do not breathe aerosols or vapours.
Ensure adequate ventilation
Avoid contact with skin and eyes.
Wash thoroughly after use
Wear protective gloves/protective clothing/eye protection/face protection.
Eyewash bottles should be available

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.
Keep out of reach of children.

7.3. Specific end use(s)

Conduction electric/thermal

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits :

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	TWA	100 ppm
		STEL	150 ppm



Productname : EMV 35 **Creationdate :** 09.11.11 Version : 1.0
Ref.Nr.: BDS000771_3_20111109 **Replaces:** AB27750

propyl acetate	109-60-4	TWA	840 mg/m3
		STEL	840 mg/m3
dimethyl ether	115-10-6	TWA	1000 ppm
isopentyl acetate	123-92-2	TWA	50 ppm
		STEL	100 ppm
butanone; ethyl methyl ketone	78-93-3	TWA	200 ppm
		STEL	300 ppm
National established exposure limits, United Kingdom			
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	TWA	100 ppm
		STEL	150 ppm
dimethyl ether	115-10-6	TWA	400 ppm
		STEL	500 ppm
n-butyl acetate	123-86-4	TWA	150 ppm
		STEL	200 ppm
Copper	7440-50-8	TWA	1 mg/m3
		STEL	2 mg/m3
butanone; ethyl methyl ketone	78-93-3	TWA	200 ppm
		STEL	300 ppm

8.2. Exposure controls

Control procedures :	Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges
Personal protection :	Take precautions to avoid contact with skin and eyes when handling the product. Ensure adequate ventilation
inhalation :	In case of insufficient ventilation, wear suitable respiratory equipment. Air purifying respirator equipped with organic gas/vapor cartridge (type A or AX)
hands and skin :	Wear suitable protective gloves (nitrile)
eyes :	Wear safety goggles.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Apperance : physical state :	DME propelled liquid.
colour :	Copper.
odour :	Solvent.
pH :	Not applicable.



Productname :	EMV 35	Creationdate :	09.11.11 Version : 1.0
Ref.Nr.:	BDS000771_3_20111109	Replaces:	AB27750

Boiling point/range :	Not available.
Flash point :	< 0 °C (Closed Cup)
Evaporation rate :	Not available.
Explosion limits : upper limit :	Not available.
lower limit :	Not available.
Vapour pressure :	Not available.
Relative density :	1.3 g/cm ³ (@ 20°C).
Solubility in water :	Insoluble in water
Auto-ignition :	> 150 °C
Viscosity :	Not applicable.

9.2. Other information

VOC: blank

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO₂

SECTION 11: Toxicological information

11.1. Information on toxicological effects



Productname : EMV 35

Creationdate :

09.11.11 Version :

1.0

Ref.Nr.: BDS000771_3_20111109

Replaces:

AB27750

Inhalation : Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion : May cause gastrointestinal disturbances
Skin contact : May cause irritation.
Eye contact : Irritating to eyes

Toxicological data :

Hazardous ingredient	CAS-nr.	method	
n-butyl acetate	123-86-4	LD50 oral rat	> 2000 mg/kg
		LC50 inhal.rat	> 20 mg/l
butanone; ethyl methyl ketone	78-93-3	LD50 oral rat	>2000 mg/kg

SECTION 12: Ecological information**12.1. Toxicity**

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
n-butyl acetate	123-86-4	IC50 algae	647 mg/l
		LC50 fish	18 mg/l
		EC50 daphnia	44 mg/l

12.2. Persistence and degradability

No experimental data available

12.3. Bioaccumulative potential

No experimental data available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available



Productname : EMV 35**Creationdate :**

09.11.11 Version :

1.0

Ref.Nr.: BDS000771_3_20111109**Replaces:**

AB27750

12.6. Other adverse effects**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

Product : This material and its container must be disposed of in a safe way.
Do not discharge into drains or the environment, dispose to an authorised waste collection point.

Contaminated packaging : Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information**14.1. UN number**

UN-number : 1950

14.2. UN proper shipping name

Proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es)Class: 2.1
ADR/RID - Classification code: 5F**14.4. Packing group**

Packing group: Not applicable.

14.5. Environmental hazardsADR/RID - Environmentally hazardous: No
IMDG - Marine pollutant: No
IATA/ICAO - Environmentally hazardous: No**14.6. Special precautions for user**ADR/RID - Tunnelcode: (D)
IMDG - Ems: F-D,S-U
IATA/ICAO - PAX: 203
IATA/ICAO - CAO: 203

Productname :	EMV 35	Creationdate :	09.11.11 Version : 1.0
Ref.Nr.:	BDS000771_3_20111109	Replaces:	AB27750

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.
Dir. 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.
EU-directive 99/45/EC
Regulation (EC) No 1907/2006 (REACH)

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation risk-phrases:

- R10: Flammable.
- R11: Highly flammable.
- R12: Extremely flammable.
- R22: Harmful if swallowed.
- R34: Causes burns.
- R36: Irritating to eyes.
- R66: Repeated exposure may cause skin dryness or cracking.
- R67: Vapours may cause drowsiness and dizziness.
- R36/37/38: Irritating to eyes, respiratory system and skin.
- R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

*Explanation hazard statements:

- H220 : Extremely flammable gas.
- H225 : Highly flammable liquid and vapour.
- H226 : Flammable liquid and vapour.
- H319 : Causes serious eye irritation.
- H336 : May cause drowsiness or dizziness.

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.