



30 Watt Universal 3-Wire Input Adapter

PSC30U-V Adapter Series Meets EISA and ENERGY STAR Requirements



Features

- Non-vented/Spill-proof Case
- EISA Energy Efficient Compliance
- ENERGY STAR EPS2.0 Compliance
- Class B EMI
- Low Profile Design

Applications

- Portable Equipment
- Peripherals
- Networking
- Gaming Machines

Safety Approvals

- cUL/UL 60950-1
- TUV 60950-1
- CE
- SAA
- C-Tick

Mechanical Characteristics

- Length: 116.5mm (4.59in)
- Width: 55mm (2.17in)
- Height: 31.5mm (1.24in)
- Weight: 250g (8.82oz.)

Output Specifications

Model	DC Output Voltage	Load		Ripple (1) P-P (max.)	Regulation		Efficiency Level
		Min.	Max.		Line	Load	
PSC30U-120V	+12V	0A	2.5A	120mV	±5%		V
PSC30U-240V	+24V	0A	1.25A	240mV	±5%		V
PSC30U-480V	+48V	0A	0.625A	480mV	±5%		V

(1) Measured with using 12-inch twisted pair terminated with a 10uF capacitor and 0.1uF ceramic in parallel.

Phihong reserves the right to make changes without further notice. Please consult Phihong USA and visit www.phihong.com for the most up-to-date specifications.

INPUT:

AC Input Voltage Rating
100 to 240VAC

AC Input Voltage Range
90 to 264VAC

AC Input Frequency
47 to 63Hz

Input Current
0.8A (rms) max. @ 115VAC
0.4A (rms) max. @ 230VAC

Leakage Current
3.5mA Max.

Inrush Current (cold)
30A for 115VAC at max. load
60A for 230VAC at max. load
(Cold start @ ambient 25°C)

Input Power Saving
0.3W maximum at no load

OUTPUT:

Efficiency
> 83.5% average efficiency

Hold-up Time
10mS Min. @ 120VAC and Max. load

Over-voltage Protection

Output shuts down and recovers after reset AC power

Over-current Protection

Output equipped with short circuit protection – auto restart

Short Circuit Protection

Output can be shorted without damage

ENVIRONMENTAL:

Temperature

Operation 0 to +40°C
Non-operation -30 to +85°C

Humidity

Operation 5 to 90%

Emissions

FCC Class B
EN55022 Class B

Dielectric Withstand (Hi-pot) Test

Primary to Secondary: 1500VAC for 1 minute, 10mA

Dimension Diagram Unit: mm

