SAFETY DATA SHEET SURFACE MOUNT ADHESIVE

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME SURFACE MOUNT ADHESIVE

PRODUCT NO. ESMA10SL

SUPPLIER ELECTROLUBE. A division of HK

WENTWORTH LTD

KINGSBURY PARK, MIDLAND ROAD

SWADLINCOTE

DERBYSHIRE, DE11 0AN UNITED KINGDOM +44(0)1283 222 111 +44(0)1283 550 177

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
Aliphatic Amines			10-30%	Xi;R36/37.
EPOXY RESIN (Number average MW <= 700)	500-033-5	25068-38-6	60-100%	R43 Xi;R36/38 N;R51/53
NEOPENTYL GLYCOL DIGLYCIDYL ETHER	241-536-7	17557-23-2	10-30%	Xi;R38. R43.

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels

3 HAZARDS IDENTIFICATION

May cause sensitisation by skin contact. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xi;R36/38. R43. N;R51/53.

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Promptly get affected person to drink large volumes of water to dilute the swallowed chemical. Get medical attention immediately! Provide rest, warmth and fresh air.

SKIN CONTACT

Remove affected person from source of contamination. Get medical attention promptly if symptoms occur after washing. Rinse the skin immediately with lots of water. Get medical attention if any discomfort continues.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Foam. Alcohol resistant foam. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES

Use water to keep fire exposed containers cool and disperse vapours.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Keep combustibles away from spilled material. Stop leak if possible without risk. DO NOT touch spilled material! Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage. Runoff or release to sewer, waterway or ground is forbidden. Inform Authorities if large amounts are involved.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame.

SURFACE MOUNT ADHESIVE

STORAGE PRECAUTIONS

Store in tightly closed original container in a cool, dry well-ventilated place. Keep in original container.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENT COMMENTS
WEL = Workplace Exposure Limits
PROTECTIVE EQUIPMENT





ENGINEERING MEASURES

No specific ventilation requirements noted, except this product must not be used in a confined space without good ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Use approved safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Paste COLOUR Red

SOLUBILITY Insoluble in water

RELATIVE DENSITY 1.18 @ 20 °c VISCOSITY 1450 mPas @ 20 °c

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid contact with acids and oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2). Nitrous gases (NOx).

11 TOXICOLOGICAL INFORMATION

HEALTH WARNINGS

INGESTION. May cause stomach pain or vomiting. Pulmonary sensitiser. SKIN CONTACT. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause sensitisation by skin contact. This chemical may cause skin/eye irritation and burns (corrosive). May cause skin irritation/eczema. INHALATION. Severe pulmonary irritant. May cause irritation to the respiratory system. EYE CONTACT. May cause severe irritation to eyes.

EYES, NOSE AND MOUTH. Repeated exposure may cause chronic eye irritation. SKIN. Mild dermatitis, allergic skin rash. Defatting, drying and cracking of skin.

ROUTE OF ENTRY

Inhalation. Ingestion. Skin and/or eye contact.

TARGET ORGANS

Eyes. Gastro-intestinal tract. Respiratory system, lungs. Skin.

MEDICAL SYMPTOMS

Severe pulmonary irritation. General respiratory distress, unproductive cough. Nausea, vomiting.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment if discharged into watercourses.

SURFACE MOUNT ADHESIVE

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



UK ROAD CLASS 9

PROPER SHIPPING NAME ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average

MW <= 700))

UK ROAD PACK GR. III ADR CLASS NO. 9

ADR CLASS Class 9: Miscellaneous ADR PACK GROUP III dangerous substances and

articles.

HAZARD No. (ADR) 90 ADR LABEL NO. 9

HAZCHEM CODE 2X CEFIC TEC(R) NO. 90GM6-III

RID CLASS NO. 9 RID PACK GROUP III UN NO. SEA 3082 IMDG CLASS 9

 IMDG PACK GR.
 III
 EMS
 F-A; S-F

 MFAG
 See Guide
 MARINE POLLUTANT
 No.

 UN NO. AIR
 3082
 ICAO CLASS
 9

AIR PACK GR. III

15 REGULATORY INFORMATION

LABELLING



Irritant



Dangerous for the environment

CONTAINS EPOXY RESIN (Number average MW <= 700)

NEOPENTYL GLYCOL DIGLYCIDYL ETHER

RISK PHRASES

R43 May cause sensitisation by skin contact.

R36/38 Irritating to eyes and skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

SAFETY PHRASES

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S37 Wear suitable gloves.

P5 Contains epoxy constituents. See information supplied by the manufacturer.

UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging) Regulations. The Control of Substances Hazardous to Health Regulations 1988.

ENVIRONMENTAL LISTING

Control of Pollution Act 1974. Control of Pollution (Special Waste Regulations) Act 1980. Rivers (Prevention of Pollution) Act 1961.

EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EEC. System of specific information relating to Dangerous Preparations. 2001/58/EEC.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

SURFACE MOUNT ADHESIVE

16 OTHER INFORMATION

GENERAL INFORMATION

CN No 39073000 ISSUED BY

Helen O'Reilly

REVISION DATE SEPTEMBER 2005

REV. NO./REPL. SDS GENERATED 2

SDS NO. 10445

RISK PHRASES IN FULL

R36/37 Irritating to eyes and respiratory system.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.