


## Lead (Pb)-free Thick Film, Rectangular Chip Resistors



### FEATURES

- High volume product suitable for commercial and special applications
- Excellent stability ( $\Delta R/R \leq 1\%$  for 1000 h at 70 °C)
- Compliant with “Restriction of the use of Hazardous Substances” (RoHS) directive 2002/95/EC (issue 2004)
- Lead (Pb)-free solder contacts on Ni barrier layer
- Pure tin plating provides compatibility with lead (Pb)-free and lead containing soldering processes
- Metal glaze on high quality ceramic
- Protective overglaze



| STANDARD ELECTRICAL SPECIFICATIONS   |      |        |   |  |                                  |                               |                              |               |
|--|------|--------|---|--|----------------------------------|-------------------------------|------------------------------|---------------|
| MODEL  | SIZE |        | POWER RATING<br>$P_{70^\circ\text{C}}$<br>W | LIMITING ELEMENT VOLTAGE<br>MAX. V $\cong$ | TEMPERATURE COEFFICIENT<br>ppm/K | TOLERANCE<br>%                | RESISTANCE RANGE<br>$\Omega$ | E-SERIES      |
|  | INCH | METRIC |   |  |                                  |                               |                              |               |
| CRCW0201   | 0201 | 0525   | 0.05  | 30   | $\pm 100$<br>$\pm 200$           | $\pm 1$<br>$\pm 1$<br>$\pm 5$ | 47R - 1M0<br>10R - 1M0       | 24 + 96       |
|  |      |        |   |  |                                  |                               |                              | 24 + 96<br>24 |
| Zero-Ohm-Resistor: $R_{\text{max.}} = 50 \text{ m}\Omega$ , $I_{\text{max.}}$ at 70 °C = 1.0 A |      |        |   |  |                                  |                               |                              |               |
| D10/CRCW0402   | 0402 | 1005   | 0.063                                       | 50   | $\pm 100$<br>$\pm 200$           | $\pm 1$<br>$\pm 5$            | 1R0 - 10M                    | 24 + 96       |
|  |      |        |   |  |                                  |                               |                              | 24            |
| Zero-Ohm-Resistor: $R_{\text{max.}} = 20 \text{ m}\Omega$ , $I_{\text{max.}}$ at 70 °C = 1.5 A |      |        |   |  |                                  |                               |                              |               |
| D11/CRCW0603   | 0603 | 1608   | 0.10  | 75   | $\pm 100$<br>$\pm 200$           | $\pm 1$<br>$\pm 5$            | 1R0 - 10M                    | 24 + 96       |
|  |      |        |   |  |                                  |                               |                              | 24            |
| Zero-Ohm-Resistor: $R_{\text{max.}} = 20 \text{ m}\Omega$ , $I_{\text{max.}}$ at 70 °C = 2.0 A |      |        |   |  |                                  |                               |                              |               |
| D12/CRCW0805   | 0805 | 2012   | 0.125                                       | 150  | $\pm 100$<br>$\pm 200$           | $\pm 1$<br>$\pm 5$            | 1R0 - 10M                    | 24 + 96       |
|  |      |        |   |  |                                  |                               |                              | 24            |
| Zero-Ohm-Resistor: $R_{\text{max.}} = 20 \text{ m}\Omega$ , $I_{\text{max.}}$ at 70 °C = 2.5 A |      |        |   |  |                                  |                               |                              |               |
| D25/CRCW1206   | 1206 | 3216   | 0.25  | 200  | $\pm 100$<br>$\pm 200$           | $\pm 1$<br>$\pm 5$            | 1R0 - 10M                    | 24 + 96       |
|  |      |        |   |  |                                  |                               |                              | 24            |
| Zero-Ohm-Resistor: $R_{\text{max.}} = 20 \text{ m}\Omega$ , $I_{\text{max.}}$ at 70 °C = 3.5 A |      |        |   |  |                                  |                               |                              |               |
| CRCW1210   | 1210 | 3225   | 0.33  | 200  | $\pm 100$<br>$\pm 200$           | $\pm 1$<br>$\pm 5$            | 1R0 - 10M                    | 24 + 96       |
|  |      |        |   |  |                                  |                               |                              | 24            |
| Zero-Ohm-Resistor: $R_{\text{max.}} = 20 \text{ m}\Omega$ , $I_{\text{max.}}$ at 70 °C = 4.0 A |      |        |   |  |                                  |                               |                              |               |
| CRCW1218   | 1218 | 3246   | 1.0   | 200  | $\pm 100$<br>$\pm 200$           | $\pm 1$<br>$\pm 5$            | 1R0 - 2M2                    | 24 + 96       |
|  |      |        |   |  |                                  |                               |                              | 24            |
| Zero-Ohm-Resistor: $R_{\text{max.}} = 20 \text{ m}\Omega$ , $I_{\text{max.}}$ at 70 °C = 7.0 A |      |        |   |  |                                  |                               |                              |               |
| CRCW2010   | 2010 | 5025   | 0.50  | 400  | $\pm 100$<br>$\pm 200$           | $\pm 1$<br>$\pm 5$            | 1R0 - 10M                    | 24 + 96       |
|  |      |        |   |  |                                  |                               |                              | 24            |
| Zero-Ohm-Resistor: $R_{\text{max.}} = 20 \text{ m}\Omega$ , $I_{\text{max.}}$ at 70 °C = 5.0 A |      |        |   |  |                                  |                               |                              |               |
| CRCW2512   | 2512 | 6332   | 1.0   | 500  | $\pm 100$<br>$\pm 200$           | $\pm 1$<br>$\pm 5$            | 1R0 - 10M                    | 24 + 96       |
|  |      |        |   |  |                                  |                               |                              | 24            |
| Zero-Ohm-Resistor: $R_{\text{max.}} = 20 \text{ m}\Omega$ , $I_{\text{max.}}$ at 70 °C = 7.0 A |      |        |   |  |                                  |                               |                              |               |

### Notes

- These resistors do not feature a limited lifetime when operated within the permissible limits. However, resistance value drift increasing over operating time may result in exceeding a limit acceptable to the specific application, thereby establishing a functional lifetime.
- Marking and packaging: See appropriate catalog or web pages
- Power rating depends on the max. temperature at the solder point, the component placement density and the substrate material

| TECHNICAL SPECIFICATIONS                  |                   |                    |                        |                  |                  |                  |          |          |          |          |
|---|-------------------|--------------------|------------------------|------------------|------------------|------------------|----------|----------|----------|----------|
| PARAMETER                                 | UNIT              | CRCW0201           | D10/<br>CRCW0402       | D11/<br>CRCW0603 | D12/<br>CRCW0805 | D25/<br>CRCW1206 | CRCW1210 | CRCW1218 | CRCW2010 | CRCW2512 |
| Rated Dissipation at 70 °C <sup>(3)</sup> | W                 | 0.05               | 0.063                  | 0.10             | 0.125            | 0.25             | 0.33     | 1.0      | 0.5      | 1.0      |
| Limiting Element Voltage <sup>(2)</sup>   | V <sub>≅</sub>    | 30                 | 50                     | 75               | 150              | 200              | 200      | 200      | 400      | 500      |
| Insulation Voltage (1 min)                | V <sub>peak</sub> | 50                 | > 75                   | > 100            | > 200            | > 300            | > 300    | > 300    | > 300    | > 300    |
| Thermal Resistance <sup>(1)</sup>         | K/W               |                    | ≤ 870                  | ≤ 550            | ≤ 440            | ≤ 220            | ≤ 140    | ≤ 65     | ≤ 88     | ≤ 65     |
| Insulation Resistance                     | Ω                 | > 10 <sup>9</sup>  |                        |                  |                  |                  |          |          |          |          |
| Category Temperature Range                | °C                | - 55/+ 125 (+ 155) |                        |                  |                  |                  |          |          |          |          |
| Failure Rate                              | h <sup>-1</sup>   | 1.10 <sup>-9</sup> | 0.3 x 10 <sup>-9</sup> |                  |                  |                  |          |          |          |          |
| Weight/1000 pieces                        | g                 | 0.17               | 0.65                   | 2                | 5.5              | 10               | 16       | 29.5     | 25.5     | 40.5     |

**Notes**



- (1) For sizes 0402 until 1206 the measuring conditions are in acc. to EN 140401-802. For all other sizes the result depends on the solder pad dimensions.
- (2) Rated voltage:  $\sqrt{P \times R}$
- (3) The power dissipation on the resistor generates a temperature rise against the local ambient, depending on the heat flow support of the printed-circuit board (thermal resistance). The rated dissipation applies only if the permitted film temperature of 155 °C is not exceeded.

| PART NUMBER AND PRODUCT DESCRIPTION  |   |  |   |   |   |  |   |   |                                     |   |   |   |   |   |   |  |  |
|--|---|--|---|---|---|--|---|---|-------------------------------------|---|---|---|---|---|---|--|--|
| PART NUMBER: CRCW0603562RFKEC <sup>(4)</sup>   |   |  |   |   |   |  |   |   |                                     |   |   |   |   |   |   |  |  |
| C  | R   | C  | W | 0   | 6 | 0  | 3 | 5 | 6                                   | 2 | R | F | K | E | C |  |  |
| MODEL  | VALUE   | TOLERANCE  |   | TCR   |   | PACKAGING <sup>(5)</sup>   |   |   | SPECIAL                             |   |   |   |   |   |   |  |  |
| CRCW0201<br>CRCW0402<br>CRCW0603<br>CRCW0805<br>CRCW1206<br>CRCW1210<br>CRCW1218<br>CRCW2010<br>CRCW2512                 | R = Decimal<br>K = Thousand<br>M = Million<br>0000 = Jumper | F = ± 1.0 %<br>J = ± 5.0 %<br>Z = Jumper                                 |   | K = ± 100 ppm/K<br>N = ± 200 ppm/K<br>0 = Jumper<br>S = Special |   | EA, EB,<br>EC, ED,<br>EE, EF,<br>EG, EH,<br>EI, EK,<br>EL, EY        |   |   | Up to 2 digits                      |   |   |   |   |   |   |  |  |
| PRODUCT DESCRIPTION: D11/CRCW0603 100 562R 1% ET6 e3   |   |  |   |   |   |  |   |   |                                     |   |   |   |   |   |   |  |  |
| D11/CRCW0603   | 100   | 562R   |   | 1 %   |   | ET6  |   |   | e3                                  |   |   |   |   |   |   |  |  |
| MODEL  | TCR   | RESISTANCE VALUE   |   | TOLERANCE   |   | PACKAGING <sup>(5)</sup>   |   |   | LEAD (Pb)-FREE                      |   |   |   |   |   |   |  |  |
| CRCW0201<br>D10/CRCW0402<br>D11/CRCW0603<br>D12/CRCW0805<br>D25/CRCW1206<br>CRCW1210<br>CRCW1218<br>CRCW2010<br>CRCW2512 | ± 200 ppm/K<br>± 100 ppm/K                                  | 10R = 10 Ω<br>562R = 562 Ω<br>10K = 10.0 kΩ<br>1M = 1 MΩ<br>0R0 = Jumper |   | ± 5 %<br>± 1 %  |   | ET1, ET5<br>ET6, ET7<br>EF4, E02<br>E67, E82<br>EG1, ET9<br>E20, E27 |   |   | e3 = Pure tin<br>Termination finish |   |   |   |   |   |   |  |  |

**Notes**

- (4) Preferred way for ordering products is by use of the PART NUMBER
- (5) Please refer to table PACKAGING, see next page

| PACKAGING    |            |               |       |              |                |         |               |         |        |                |               |
|--------------|------------|---------------|-------|--------------|----------------|---------|---------------|---------|--------|----------------|---------------|
| MODEL        | REEL       |               |       |              |                |         |               |         | BULK   |                |               |
|              | TAPE WIDTH | DIAMETER      | PITCH | PIECES/ REEL | PACKAGING CODE |         |               |         | PIECES | PACKAGING CODE |               |
|              |            |               |       |              | PART NUMBER    |         | PRODUCT DESC. |         |        | PART NUMBER    | PRODUCT DESC. |
|              |            |               |       |              | PAPER          | BLISTER | PAPER         | BLISTER |        |                |               |
| CRCW0201     | 8 mm       | 180 mm/7"     | 2 mm  | 10 000       | ED             |         | ET7           |         |        |                |               |
|              |            | 330 mm/13"    | 2 mm  | 50 000       | EE             |         | EF4           |         |        |                |               |
| D10/CRCW0402 | 8 mm       | 180 mm/7"     | 2 mm  | 10 000       | ED             |         | ET7           |         | 50 000 | EY             | E27           |
|              |            | 330 mm/13"    | 2 mm  | 50 000       | EE             |         | EF4           |         |        |                |               |
| D11/CRCW0603 | 8 mm       | 180 mm/7"     | 4 mm  | 5000         | EA             | EI      | ET1           | EG1     | 25 000 | EY             | E27           |
|              |            | 285 mm/11.25" | 4 mm  | 10 000       | EB             |         | ET5           |         |        |                |               |
|              |            | 330 mm/13"    | 4 mm  | 20 000       | EC             | EL      | ET6           | E20     |        |                |               |
| D12/CRCW0805 | 8 mm       | 180 mm/7"     | 4 mm  | 5000         | EA             | EI      | ET1           | EG1     | 10 000 | EY             | E27           |
|              |            | 285 mm/11.25" | 4 mm  | 10 000       | EB             |         | ET5           |         |        |                |               |
|              |            | 330 mm/13"    | 4 mm  | 20 000       | EC             | EL      | ET6           | E20     |        |                |               |
| D25/CRCW1206 | 8 mm       | 180 mm/7"     | 4 mm  | 5000         | EA             | EI      | ET1           | EG1     |        |                |               |
|              |            | 285 mm/11.25" | 4 mm  | 10 000       | EB             |         | ET5           |         |        |                |               |
|              |            | 330 mm/13"    | 4 mm  | 15 000       |                | EL      |               | E20     |        |                |               |
|              |            | 330 mm/13"    | 4 mm  | 20 000       | EC             |         | ET6           |         |        |                |               |
| CRCW1210     | 12 mm      | 180 mm/7"     | 4 mm  | 5000         | EA             |         | ET1           |         |        |                |               |
|              |            | 285 mm/11.25" | 4 mm  | 10 000       | EB             |         | ET5           |         |        |                |               |
|              |            | 330 mm/13"    | 4 mm  | 20 000       | EC             |         | ET6           |         |        |                |               |
| CRCW1218     | 12 mm      | 180 mm/7"     | 4 mm  | 4000         |                | EK      |               | ET9     |        |                |               |
| CRCW2010     | 12 mm      | 180 mm/7"     | 4 mm  | 4000         |                | EF      |               | E02     |        |                |               |
| CRCW2512     | 12 mm      | 180 mm/7"     | 8 mm  | 2000         |                | EG      |               | E67     |        |                |               |
|              |            |               | 4 mm  | 4000         |                | EH      |               | E82     |        |                |               |


**DIMENSIONS**


| SIZE |        | DIMENSIONS [in millimeters]              |             |             |   |  | SOLDER PAD DIMENSIONS [in millimeters] |      |      |                |     |     |
|------|--------|--|-------------|-------------|---|--|--|------|------|----------------|-----|-----|
|      |        |  |             |             |   |  | REFLOW SOLDERING                       |      |      | WAVE SOLDERING |     |     |
| INCH | METRIC | L  | W           | H           | T1                                      | T2                                       | a                                      | b    | l    | a              | b   | l   |
| 0201 | 0525   | 0.6 ± 0.05                               | 0.3 ± 0.05  | 0.23 ± 0.05 | 0.15 ± 0.05                             | 0.15 <sup>+0.05</sup> / <sub>-0.10</sub> | 0.28                                   | 0.43 | 0.23 |                |     |     |
| 0402 | 1005   | 1.0 ± 0.05                               | 0.5 ± 0.05  | 0.35 ± 0.05 | 0.25 ± 0.05                             | 0.2 ± 0.1                                | 0.4                                    | 0.6  | 0.5  |                |     |     |
| 0603 | 1608   | 1.55 <sup>+0.10</sup> / <sub>-0.05</sub> | 0.85 ± 0.1  | 0.45 ± 0.05 | 0.3 ± 0.2                               | 0.3 ± 0.2                                | 0.5                                    | 0.9  | 1.0  | 0.9            | 0.9 | 1.0 |
| 0805 | 2012   | 2.0 <sup>+0.20</sup> / <sub>-0.10</sub>  | 1.25 ± 0.15 | 0.45 ± 0.05 | 0.3 <sup>+0.20</sup> / <sub>-0.10</sub> | 0.3 ± 0.2                                | 0.7                                    | 1.3  | 1.2  | 0.9            | 1.3 | 1.3 |
| 1206 | 3216   | 3.2 <sup>+0.10</sup> / <sub>-0.20</sub>  | 1.6 ± 0.15  | 0.55 ± 0.05 | 0.45 ± 0.2                              | 0.4 ± 0.2                                | 0.9                                    | 1.7  | 2.0  | 1.1            | 1.7 | 2.3 |
| 1210 | 3225   | 3.2 ± 0.2                                | 2.5 ± 0.2   | 0.55 ± 0.05 | 0.45 ± 0.2                              | 0.4 ± 0.2                                | 0.9                                    | 2.5  | 2.0  | 1.1            | 2.5 | 2.2 |
| 1218 | 3246   | 3.2 <sup>+0.10</sup> / <sub>-0.20</sub>  | 4.6 ± 0.15  | 0.55 ± 0.05 | 0.45 ± 0.2                              | 0.4 ± 0.2                                | 1.05                                   | 4.9  | 1.9  | 1.25           | 4.8 | 1.9 |
| 2010 | 5025   | 5.0 ± 0.15                               | 2.5 ± 0.15  | 0.6 ± 0.1   | 0.6 ± 0.2                               | 0.6 ± 0.2                                | 1.0                                    | 2.5  | 3.9  | 1.2            | 2.5 | 3.9 |
| 2512 | 6332   | 6.3 ± 0.2                                | 3.15 ± 0.15 | 0.6 ± 0.1   | 0.6 ± 0.2                               | 0.6 ± 0.2                                | 1.0                                    | 3.2  | 5.2  | 1.2            | 3.2 | 5.2 |




**FUNCTIONAL PERFORMANCE**

**Single Pulse**




Maximum pulse load, single pulse; applicable if  $\bar{P} \rightarrow 0$  and  $n \leq 1000$  and  $\hat{U} \leq \hat{U}_{max}$ ; for permissible resistance change equivalent to 8000 h operation

**Continuous Pulse**




Maximum pulse load, continuous pulses; applicable if  $\bar{P} \leq P(\vartheta_{amb})$  and  $\hat{U} \leq \hat{U}_{max}$ ; for permissible resistance change equivalent to 8000 h operation


**Pulse Voltage**




Maximum pulse voltage, single and continuous pulses; applicable if  $\hat{P} \leq \hat{P}_{max}$ ; for permissible resistance change equivalent to 8000 h operation




Temperature Rise







Derating




Non-Linearity



Current Noise



Stability nomogram typical values (for handling see general explanations)



Power rating as a function of packaging density (guideline)



| <b>TEST PROCEDURES AND REQUIREMENTS</b>          |  |   |                               |  |
|--|--|---|-------------------------------|--|
| EN 60115-1                                       |  |   |                               | SIZE 0201 ONLY                                   |
| TEST (clause)                                    | CONDITIONS OF TEST   | REQUIREMENTS PERMISSIBLE CHANGE ( $\Delta R/R$ )      |                               | REQUIREMENTS PERMISSIBLE CHANGE ( $\Delta R/R$ ) |
|  |  | STABILITY CLASS 1 OR BETTER                           | STABILITY CLASS 2 OR BETTER   |  |
|  | Stability for product types:   |   |                               |  |
|  | <b>D../CRCW....e3</b>  | 1 $\Omega$ to 10 M $\Omega$                           | 1 $\Omega$ to 10 M $\Omega$   | 10 $\Omega$ to 1 M $\Omega$                      |
| Resistance (4.5)                                 | -  | $\pm 1\%$   | $\pm 5\%$                     | $\pm 1\%$ ; $\pm 5\%$                            |
| Temperature coefficient (4.8.4.2)                | 20/- 55/20 $^{\circ}\text{C}$ and 20/125/20 $^{\circ}\text{C}$   | $\pm 100$ ppm/K                                       | $\pm 200$ ppm/K               | $\pm 200$ ppm/K                                  |
| Overload (4.13)                                  | $U = 2.5 \times (P_{70} \times R)^{1/2} \leq 2 \times U_{\text{max}}$ ;<br>Duration: according the style   | $\pm (0.25\% R + 0.05 \Omega)$                        | $\pm (0.5\% R + 0.05 \Omega)$ | $\pm (1\% R + 0.05 \Omega)$                      |
| Solderability (4.17.5)                           | Aging 4 h at 155 $^{\circ}\text{C}$ , dryheat dolder bath method; 235 $^{\circ}\text{C}$ ; 2 s visual examination  | Good tinning ( $\geq 95\%$ covered) no visible damage |                               |  |
| Resistance to soldering heat (4.18.2)            | Solder bath method; (260 $\pm 5$ ) $^{\circ}\text{C}$ ; (10 $\pm 1$ ) s  | $\pm (0.25\% R + 0.05 \Omega)$                        | $\pm (0.5\% R + 0.05 \Omega)$ | $\pm (1\% R + 0.05 \Omega)$                      |
| Rapid change of temperature (4.19)               | 30 min at LCT = - 55 $^{\circ}\text{C}$ ; 30 min at UCT = 125 $^{\circ}\text{C}$ ; 5 cycles  | $\pm (0.25\% R + 0.05 \Omega)$                        | $\pm (0.5\% R + 0.05 \Omega)$ | $\pm (0.5\% R + 0.05 \Omega)$                    |
| Damp heat, steady state (4.24)                   | (40 $\pm 2$ ) $^{\circ}\text{C}$ ; 56 days; (93 $\pm 3$ ) % RH   | $\pm (1\% R + 0.05 \Omega)$                           | $\pm (2\% R + 0.1 \Omega)$    | $\pm (2\% R + 0.1 \Omega)$                       |
| Climatic sequence (4.23)                         | 16 h at UCT = 125 $^{\circ}\text{C}$ ; 1 cycle at 55 $^{\circ}\text{C}$ ; 2 h at LCT = - 55 $^{\circ}\text{C}$ ; 1 h/1 kPa at 15 $^{\circ}\text{C}$ to 35 $^{\circ}\text{C}$ ; 5 cycles at 55 $^{\circ}\text{C}$<br>$U = (P_{70} \times R)^{1/2}$<br>$U = U_{\text{max}}$ ; whichever is less severe | $\pm (1\% R + 0.05 \Omega)$                           | $\pm (2\% R + 0.1 \Omega)$    | $\pm (2\% R + 0.1 \Omega)$                       |
| Endurance at 70 $^{\circ}\text{C}$ (4.25.1)      | $U = (P_{70} \times R)^{1/2}$<br>$U = U_{\text{max}}$ ; whichever is less severe<br>1.5 h on; 0.5 h off; 70 $^{\circ}\text{C}$ ; 1000 h  | $\pm (1\% R + 0.05 \Omega)$                           | $\pm (2\% R + 0.1 \Omega)$    | $\pm (3\% R + 0.1 \Omega)$                       |
| Extended endurance (4.25.1.8)                    | Duration extended to 8000 h  | $\pm (2\% R + 0.1 \Omega)$                            | $\pm (4\% R + 0.1 \Omega)$    | $\pm (4\% R + 0.1 \Omega)$                       |
| Endurance at upper category temperature (4.25.3) | UCT = 125 $^{\circ}\text{C}$ ; 1000 h  | $\pm (1\% R + 0.05 \Omega)$                           | $\pm (2\% R + 0.1 \Omega)$    | $\pm (2\% R + 0.1 \Omega)$                       |

| <b>APPLICABLE SPECIFICATIONS</b> |  |
|----------------------------------|--|
| • EN 60115-1                     | Generic Specification                    |
| • EN 140400                      | Sectional Specification                  |
| • EN 140401-802                  | Detail Specification                     |
| • IEC 60068-2-X                  | Variety of environmental test procedures |
| • IEC 60286-3                    | Packaging of SMD components              |



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.