



WIRING COLOR:
E: Yellow/Green
N: Blue
L: Brown

LENGED ON CORD: (凹字)

I-SHENG KSIS <VDE> KEMA-KEUR +0+0+0 <ÖVE> △ CEPEC 809 S(D)(N)(H)
NF-USE 1353 IEMMEQU H05VV-F 3G 0.75mm² 60227 IEC 53 RVV 300/500V
A041481 3ASL/75 4V-75 V-75(75°C) 250/440V ORDINARY DUTY Q88228 -LF-

No	BOM ITEM	Q' TY	P/N
1	SP-023 INSERT	1 PCS	MB023012
2	PVC 50P (SP-023)	45 g	RPP05012
3	KPR-14 BLADE	6 pcs	BBB14000
4	IS-14 INNER BODY	2pcs	MI014000
5	PVC 50P (IS-14)	28.6 g	RPP05012
6	IN-01Y INNER BODY	1set	MI01Y012
7	TERMINALGEM: 99146	3pcs	BEB99146
8	PVC 50P	38g	RPP05012
9	H05VV-F 3G 0.75 500mm	2pcs	6B3016
10	PE TIE (BLACK, 6 inch)	1 pcs	KBBPE115

CABLE	H05VV-F 3G 0.75 DENT PRINT CT-12 (BLACK)				
PLUG	SP-023 + IS-14+IS-14	LENGTH	1300	UNIT	mm
CLIENT	NAME	SACONTOP	N/W	UNIT	kg
	P/N	43-526-34	KS DWG	SR-1210018-1	VER. A
Maxxtro [®]				Design. by	TESS
				Review. by	李俊裴
				Approval. by	周家榮
P34 6B3016 12 130 00					