



WD SiliconDrive® CF

WD SiliconDrive® II CF

Advanced Solid State Storage

WD SiliconDrive CF products are ideal replacements for flash cards in critical storage applications. Advanced solid state storage technologies integrated into every WD SiliconDrive CF increase performance and reliability and deliver a lower total cost of storage ownership.

- High performance
- 24x7 reliability
- Low total cost of ownership



Product Highlights

- Multi-year product service life
- Integrated PowerArmor® and SiSMART® technologies
- Field-proven in thousands of customer applications

Product Features

PowerArmor

Eliminates drive corruption from power disturbances

SiSMART

Delivers real-time data on SSD useable life

SolidStor®

Ensures data integrity and multi-year product life

LifeEST™

Methodology forecasts SSD endurance in months or years

SiSecure® (WD SiliconDrive II only)

Protects application data and software IP

Markets

- Automotive and transportation
- Industrial automation
- Netcom
- Medical
- Video surveillance

Applications

- Diagnostic equipment
- Digital graphics
- Industrial PCs
- SAN switches
- Storage appliances
- Telecom and networking infrastructure
- Wireless infrastructure

PUT YOUR LIFE ON IT®



WD SiliconDrive CF

WD SiliconDrive II CF

Specifications ¹	WD SiliconDrive CF	WD SiliconDrive II CF
Model number	SSD-Cxxx(x)-3500	SSD-Cxxx(x)-4300
Formatted capacity range	128 MB to 8 GB	1 GB to 16 GB
Form factor	CF ATA-3	CF ATA-5
Interface	PATA	PATA
RoHS compliant ²	RoHS 6/6	RoHS 6/6
Performance		
Target Performance		
Interface Burst Speed	16.7 MB/s	66 MB/s
Sustained Read Speed	8 MB/s	34 MB/s
Sustained Write Speed	6 MB/s	19 MB/s
Operational Lifespan		
Read	Unlimited	Unlimited
Write (service life @ GB/day)	-	-
16 GB capacity	-	108.8 Years @ 402.9
8 GB capacity	324.3 Years @ 135.2	54.4 Years @ 402.9
4 GB capacity	162.2 Years @ 135.2	27.2 Years @ 402.9
2 GB capacity	81.1 Years @ 135.2	13.6 Years @ 402.9
1 GB capacity	40.5 Years @ 135.2	6.8 Years @ 402.9
512 MB capacity	20.3 Years @ 135.2	-
256 MB capacity	10.1 Years @ 135.2	-
128 MB capacity	5.1 Years @ 135.2	-
Reliability/Data Integrity		
MTBF (hours)	4,000,000	
Non-recoverable read errors per bits read	<1 in 10 ¹⁴	
Latency (Command to DRQ)	2 ms	
Limited warranty ³	5 years	
Power Management		
DC input voltage	3.3V±10% 5.0±10%	3.3V±10% 5.0±10%
Sleep (standby watts)	0.00165 0.005	0.00165 0.005
Read (peak watts)	0.2475 0.5	0.33 0.6
Write (peak watts)	0.2475 0.5	0.33 0.6
Environmental		
Operating Temperature		
Standard Temperature (C) ⁴	0°C to 70°C	
Extended Temperature (I) ⁴	-40°C to 85°C	
Non-Operating Temperature	-55°C to 125°C	
Relative Humidity	8% to 95% non-condensing	
Operating Shock	1000G, Half-sine, 0.5 ms Duration, 50g Pk, MIL-STD-810F, Method 516.5, Procedure I	
Vibration	16.3gRMS, MIL-STD-810F, Method 514.5, Procedure I, Category 24	
Altitude	80,000 ft., MIL-STD-810F, Method 500.4, Procedure II	
Physical Dimensions		
Length (in./mm, max)	1.433/36.4	1.433/36.4 mm
Width (in./mm, ± .01 in.)	1.685/42.8	1.685/42.8 mm
Height (in./mm, max)	0.130/3.3	0.130/3.3 mm
Weight (lb./gm, max)	0.05/110	0.05/110

¹As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (Gb/s) = one billion bits per second. Effective maximum SATA 3.0 Gb/s or SATA 1.5 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-IO organization as of the date of this specification sheet. Visit www.sata-io.org for details.

²WD complies with the Restriction of Hazardous Substances (RoHS) Directive 2002/95/EC of the European Parliament, which is effective in the EU beginning July 1, 2006. RoHS aims to protect human health and the environment by restricting the use of certain hazardous substances in new equipment, and consists of restrictions on lead, mercury, cadmium, and other substances.

³The term of the limited warranty may vary by region. Visit support.wdc.com/warranty for details.

⁴°C (0-70°C) or I (-40°C-85°C)

Western Digital, WD, the WD logo, SiliconDrive, PowerArmor, SolidStor, SiSecure, and SiSMART are registered trademarks in the U.S. and other countries; and FIT Lab and LifeEST are trademarks of Western Digital Technologies, Inc. Other marks may be mentioned herein that belong to other companies. Product specifications subject to change without notice.

For service and literature:

support.wdc.com

www.westerndigital.com

800.ASK.4WDC

800.832.4778

+800.6008.6008

00800.27549338

+31.880062100

North America

Spanish

Asia Pacific

Europe

(toll free where available)

Europe/Middle East/Africa



© 2010 Western Digital Technologies, Inc.
All rights reserved.

Western Digital
20511 Lake Forest Drive
Lake Forest, California 92630
U.S.A.

2879-771374-A00 Jun 2010