

SAFETY DATA SHEET

Version #: Issue date: 2,0 19-May-2021

Supersedes date:

Revision date: 17-March-2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

KONTAKT IPA

Registration number

Product registration number

 Denmark
 PR-No 1239954

 Norway
 P-312800

UFI:

Austria: P83X-38PV-Q00Y-QEHD Belgium: P83X-38PV-Q00Y-QEHD Bulgaria: P83X-38PV-Q00Y-QEHD Croatia: P83X-38PV-Q00Y-QEHD Cyprus: P83X-38PV-Q00Y-QEHD

Cyprus: P83X-38PV-Q00Y-QEHD
Czech Republic: P83X-38PV-Q00Y-QEHD
Denmark: P83X-38PV-Q00Y-QEHD
Estonia: P83X-38PV-Q00Y-QEHD
EU: P83X-38PV-Q00Y-QEHD
Finland: P83X-38PV-Q00Y-QEHD
France: P83X-38PV-Q00Y-QEHD
Germany: P83X-38PV-Q00Y-QEHD
Great Britain: P83X-38PV-Q00Y-QEHD
Hungary: P83X-38PV-Q00Y-QEHD
Hungary: P83X-38PV-Q00Y-QEHD
Italy: P83X-38PV-Q00Y-QEHD
Latvia: P83X-38PV-Q00Y-QEHD
Lithuania: P83X-38PV-Q00Y-QEHD
Luxembourg: P83X-38PV-Q00Y-QEHD
Luxembourg: P83X-38PV-Q00Y-QEHD
Luxembourg: P83X-38PV-Q00Y-QEHD

Malta: P83X-38PV-Q00Y-QEHD Netherlands: P83X-38PV-Q00Y-QEHD Norway: P83X-38PV-Q00Y-QEHD Poland: P83X-38PV-Q00Y-QEHD Portugal: P83X-38PV-Q00Y-QEHD Romania: P83X-38PV-Q00Y-QEHD Slovakia: P83X-38PV-Q00Y-QEHD Slovenia: P83X-38PV-Q00Y-QEHD Spain: P83X-38PV-Q00Y-QEHD Sweden: P83X-38PV-Q00Y-QEHD

Synonyms None.

Product code BDS000792AE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaners - Precision

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company name CRC Industries Europe by

Address Touwslagerstraat 1

9240 Zele Belgium

 Telephone
 +32(0)52/45.60.11

 Fax
 +32(0)52/45.00.34

 E-mail
 hse@crcind.com

 Website
 www.crcind.com

Material name: KONTAKT IPA - Kontakt chemie - Europe

1.4. Emergency telephone

number

Tel.: +32(0)52/45.60.11 (office hours: 9-17h CET)

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons

Information Centre

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Belgium National Poisons Control Center

070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Bulgaria National Toxicological Information Centre

+359 2 9154233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Czech Republic National Poisons Information Centre

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons Control Center

+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Estonia National Poisons Information Centre

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Hungary National Emergency Phone Number

36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Lithuania Neatidėliotina informacija apsinuodijus

+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and **Emergency Department**

2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Netherlands National Poisons Information Center (NVIC)

030-274 88 88 (Only for the purpose of informing medical personnel in cases of acute intoxications)

Norway Norwegian Poison

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Information Center Portugal Poison Centre

800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Romania Număr de telefon

021 5992300, int. 291 Spitalul Clinic de Urgență București: spital@urgentafloreasca.ro

care poate fi apelat în caz de urgență:

Romania

0265 212111, 0265 211292, 0265 217235 Spitalul Clinic Județean de Urgență Târgu Mureș: secretariat@spitjudms.ro

Slovakia National **Toxicological Information** Centre

+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Sweden National Poison Information Center

112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Switzerland Tox Info Suisse

145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Category 1 H222 - Extremely flammable Aerosols

aerosol.

H229 - Pressurized container: May

burst if heated.

Health hazards

exposure

Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Specific target organ toxicity - single Category 3 narcotic effects H336 - May cause drowsiness or

dizziness.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Propan-2-ol; Isopropyl alcohol; Isopropanol

Hazard pictograms



Signal word Danger

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurized container: May burst if heated.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

Prevention

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing mist/vapours.

P271 Use only outdoors or in a well-ventilated area.

Response Not assigned.

Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None.

2.3. Other hazards This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or

Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Propan-2-ol; Isopropyl alcohol; Isopropanol	75 - 100	67-63-0 200-661-7	01-2119457558-25	603-117-00-0	
Classification	on: Flam. Liq.	2;H225, Eye Irrit. 2;H	1319, STOT SE 3;H336		
Carbon dioxide	1 - 5	124-38-9 204-696-9	-	-	#
Classification	on: Press. Gas	s:H280			

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

ATE: Acute toxicity estimate.

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

centre or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

Extremely flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing media

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures

Specific methods

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. This product is miscible in water. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Components	e (GwV), BGBI. II, no. 184/2001 Type	Value
Carbon dioxide (CAS 124-38-9)	Ceiling	18000 mg/m3
		10000 ppm
	MAK	9000 mg/m3
		5000 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	MAK	500 mg/m3
		200 ppm
	STEL	2000 mg/m3
		800 ppm
Belgium. Exposure Limit Values		
Components	Туре	Value
Carbon dioxide (CAS 124-38-9)	STEL	54784 mg/m3
		30000 ppm
	TWA	9131 mg/m3
		5000 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3
		400 ppm
	TWA	500 mg/m3
		200 ppm
Bulgaria. OELs. Regulation No 13 Components	on protection of workers agai	nst risks of exposure to chemical agents at work Value
Carbon dioxide (CAS	TWA	9000 mg/m3
124-38-9)		
		5000 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	5000 ppm 1225 mg/m3
	STEL TWA	* *
alcohol; Isopropanol (CAS 67-63-0)	TWA	1225 mg/m3 980 mg/m3
alcohol; Isopropanol (CAS 67-63-0)	TWA	1225 mg/m3
alcohol; Isopropanol (CAS 67-63-0) Croatia. Dangerous Substance Ex	TWA posure Limit Values in the Wo	1225 mg/m3 980 mg/m3 prkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/0
alcohol; Isopropanol (CAS 67-63-0) Croatia. Dangerous Substance Ex Components Carbon dioxide (CAS	TWA posure Limit Values in the Wo	1225 mg/m3 980 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/0 Value
alcohol; Isopropanol (CAS 67-63-0) Croatia. Dangerous Substance Ex Components Carbon dioxide (CAS	TWA posure Limit Values in the Wo	1225 mg/m3 980 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/0 Value 9000 mg/m3
alcohol; Isopropanol (CAS 67-63-0) Croatia. Dangerous Substance Ex Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	TWA sposure Limit Values in the Wo Type MAC	980 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/0 Value 9000 mg/m3 5000 ppm
alcohol; Isopropanol (CAS 67-63-0) Croatia. Dangerous Substance Ex Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	TWA sposure Limit Values in the Wo Type MAC	980 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/0 Value 9000 mg/m3 5000 ppm 999 mg/m3
alcohol; Isopropanol (CAS 67-63-0) Croatia. Dangerous Substance Ex Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	TWA Eposure Limit Values in the Wo Type MAC MAC	980 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/0 Value 9000 mg/m3 5000 ppm 999 mg/m3 400 ppm
alcohol; Isopropanol (CAS 67-63-0) Croatia. Dangerous Substance Ex Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TWA Eposure Limit Values in the Work Type MAC MAC STEL	980 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/0 Value 9000 mg/m3 5000 ppm 999 mg/m3 400 ppm 1250 mg/m3
alcohol; Isopropanol (CAS 67-63-0) Croatia. Dangerous Substance Ex Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Cyprus. OELs. Control of factory	TWA Eposure Limit Values in the Wo Type MAC MAC STEL atmosphere and dangerous su	980 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/0 Value 9000 mg/m3 5000 ppm 999 mg/m3 400 ppm 1250 mg/m3 500 ppm

SDS EU

Components	Туре	Value
Carbon dioxide (CAS 124-38-9)	Ceiling	45000 mg/m3
	TWA	9000 mg/m3
Propan-2-ol; Isopropyl Ilcohol; Isopropanol (CAS 17-63-0)	Ceiling	1000 mg/m3
,	TWA	500 mg/m3
Denmark. Exposure Limit	Values	
Components	Туре	Value
Carbon dioxide (CAS 24-38-9)	TLV	9000 mg/m3
		5000 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TLV	490 mg/m3
		200 ppm
-		ostances (Regulation No. 105/2001, Annex), as amende
Components	Туре	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	600 mg/m3
		250 ppm
	TWA	350 mg/m3
		150 ppm
Finland. Workplace Expos Components	sure Limits Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m3
		5000 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	620 mg/m3
,		250 ppm
	TWA	500 mg/m3
		200 ppm
France. OELs. Indicative (Occupational Exposure Limits as Pres Type	cribed by Order of 30 June 2004, as amended Value
Carbon dioxide (CAS 124-38-9)	VME	9000 mg/m3
		9000 mg/m3
		5000 ppm
		5000 ppm
France. Threshold Limit V Components	/alues (VLEP) for Occupational Exposu Type	ure to Chemicals in France, INRS ED 984 Value
Carbon dioxide (CAS 124-38-9)	VME	9000 mg/m3
Regulatory status:	Regulatory indicative (VRI)	5000
		5000 ppm

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value

Propan-2-ol; Isopropyl VLE 980 mg/m3 alcohol; Isopropanol (CAS

67-63-0)

Regulatory status: Indicative limit (VL)

400 ppm

Regulatory status: Indicative limit (VL)

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

in the Work Area (DFG) Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m3	
,		5000 ppm	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TWA	500 mg/m3	
		200 ppm	
Germany. TRGS 900, Limit Values			
Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	AGW	9100 mg/m3	
		5000 ppm	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	AGW	500 mg/m3	
07-00-07		200 ppm	
Greece. OELs (Decree No. 90/199	9, as amended)		
Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		5000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3	
,		500 ppm	
	TWA	980 mg/m3	
		400 ppm	
Hungary. OELs. Joint Decree on (Chemical Safety of Workplace	s	
Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3	
	TWA	500 mg/m3	
Iceland. OELs. Regulation 154/19			
Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3	
		5000 ppm	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TWA	490 mg/m3	
•		200 ppm	

Material name: KONTAKT IPA - Kontakt chemie - Europe

Ireland. Occupational Exposure L Components	Туре	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
taly. Occupational Exposure Lim	its	
Components	Туре	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
	0.751	5000 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 37-63-0)	STEL	400 ppm
	TWA	200 ppm
Latvia. OELs. Occupational expos	sure limit values of chemical sub	stances in work environment
Components	Туре	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	600 mg/m3
,	TWA	350 mg/m3
Lithuania. OELs. Limit Values for	Chemical Substances, General	Requirements
Components	Туре	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	600 mg/m3
		250 ppm
	TWA	350 mg/m3
		150 ppm
Luxembourg. Binding Occupation		I), Memorial A Value
Components	Type	
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Malta. OELs. Occupational Expos Schedules I and V)	ure Limit Values (L.N. 227. of Oc	cupational Health and Safety Authority Act (CAP. 42
Components	Туре	Value
Carbon dioxide (CAS	TWA	9000 mg/m3
124-38-9)	•• •	3····-
		5000 ppm
Netherlands. OELs (binding)		
Components	Туре	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
Norway. Administrative Norms fo		
Components	Type	Value
Carbon dioxide (CAS	Type	
Components Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m3

	Value
	5000 ppm
Propan-2-ol; Isopropyl TLV Ilcohol; Isopropanol (CAS i7-63-0)	245 mg/m3
	100 ppm
oland. Ordinance of the Minister of Labour and Social Policy on 6 J	
concentrations and intensities of harmful health factors in the work of Components Type	environment, Journal of Laws 2014, item 817 Value
Carbon dioxide (CAS STEL	27000 mg/m3
24-38-9)	27000 Hig/iii3
TWA	9000 mg/m3
Propan-2-ol; Isopropyl STEL slcohol; Isopropanol (CAS s7-63-0)	1200 mg/m3
TWA	900 mg/m3
Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1	Series A. n.266)
Components Type	Value
Carbon dioxide (CAS TWA 124-38-9)	9000 mg/m3
	5000 ppm
Portugal. VLEs. Norm on occupational exposure to chemical agents Components Type	(NP 1796) Value
· · · · · · · · · · · · · · · · · · ·	
Carbon dioxide (CAS STEL 24-38-9)	30000 ppm
TWA	5000 ppm
	400 ppm
Propan-2-ol; Isopropyl STEL alcohol; Isopropanol (CAS 67-63-0)	тоо рртп
alcohol; Isopropanol (CAS	200 ppm
alcohol; Isopropanol (CAS 37-63-0) TWA	200 ppm
alcohol; Isopropanol (CAS 37-63-0) TWA Romania. OELs. Protection of workers from exposure to chemical ag	200 ppm
TWA Romania. OELs. Protection of workers from exposure to chemical accomponents Type Carbon dioxide (CAS TWA	200 ppm gents at the workplace
Icohol; Isopropanol (CAS 7-63-0) TWA Romania. OELs. Protection of workers from exposure to chemical accomponents Type Carbon dioxide (CAS TWA	200 ppm gents at the workplace Value
alcohol; Isopropanol (CAS 67-63-0) TWA Romania. OELs. Protection of workers from exposure to chemical ag Components Type	200 ppm gents at the workplace Value 9000 mg/m3
TWA Romania. OELs. Protection of workers from exposure to chemical agroup on the components Carbon dioxide (CAS TWA 24-38-9) Propan-2-ol; Isopropyl STEL Isopropanol (CAS	200 ppm gents at the workplace Value 9000 mg/m3 5000 ppm
Alcohol; Isopropanol (CAS 67-63-0) TWA Romania. OELs. Protection of workers from exposure to chemical agroup to chemical agro	200 ppm gents at the workplace Value 9000 mg/m3 5000 ppm 500 mg/m3
Alcohol; Isopropanol (CAS 67-63-0) TWA Romania. OELs. Protection of workers from exposure to chemical action of many components Type Carbon dioxide (CAS TWA 24-38-9) Propan-2-ol; Isopropyl STEL 87-63-0)	200 ppm gents at the workplace Value 9000 mg/m3 5000 ppm 500 mg/m3 203 ppm
Alcohol; Isopropanol (CAS 67-63-0) TWA Romania. OELs. Protection of workers from exposure to chemical agroup to chemical agro	200 ppm gents at the workplace Value 9000 mg/m3 5000 ppm 500 mg/m3 203 ppm 200 mg/m3 81 ppm
Alcohol; Isopropanol (CAS 67-63-0) TWA Romania. OELs. Protection of workers from exposure to chemical action of many components Type Carbon dioxide (CAS TWA 124-38-9) Propan-2-ol; Isopropyl STEL 87-63-0)	200 ppm gents at the workplace Value 9000 mg/m3 5000 ppm 500 mg/m3 203 ppm 200 mg/m3 81 ppm

5000 ppm

400 ppm

500 mg/m3 200 ppm

1000 mg/m3

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

STEL

 TWA

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3	
		5000 ppm	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TWA	500 mg/m3	
,		200 ppm	
Spain. Occupational Exposure Lir Components	nits Type	Value	
Carbon dioxide (CAS	TWA	9150 mg/m3	
124-38-9)	TWA	-	
	0.751	5000 ppm	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3	
		400 ppm	
	TWA	500 mg/m3	
		200 ppm	
Sweden. OELs. Work Environmen Components	t Authority (AV), Occupationa Type	I Exposure Limit Values (AFS 2015:7) Value	
Carbon dioxide (CAS 124-38-9)	STEL	18000 mg/m3	
		10000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	600 mg/m3	
		250 ppm	
	T\A/A	350 mg/m3	
	TWA	ooo mg/me	
	TWA	150 ppm	
	n Arbeitsplatz	150 ppm	
Components	n Arbeitsplatz Type	150 ppm Value	
Components Carbon dioxide (CAS	n Arbeitsplatz	150 ppm Value 9000 mg/m3	
Components Carbon dioxide (CAS 124-38-9)	n Arbeitsplatz Type TWA	150 ppm Value 9000 mg/m3 5000 ppm	
Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	n Arbeitsplatz Type	150 ppm Value 9000 mg/m3	
Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	n Arbeitsplatz Type TWA	150 ppm Value 9000 mg/m3 5000 ppm	
Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	n Arbeitsplatz Type TWA	150 ppm Value 9000 mg/m3 5000 ppm 1000 mg/m3	
Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	Type TWA STEL	150 ppm Value 9000 mg/m3 5000 ppm 1000 mg/m3 400 ppm	
Switzerland. SUVA Grenzwerte an Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TWA TWA	150 ppm Value 9000 mg/m3 5000 ppm 1000 mg/m3 400 ppm 500 mg/m3	
Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) UK. EH40 Workplace Exposure Li	TWA TWA	150 ppm Value 9000 mg/m3 5000 ppm 1000 mg/m3 400 ppm 500 mg/m3	
Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) UK. EH40 Workplace Exposure Licomponents Carbon dioxide (CAS	TWA TWA TWA TWA TWA TWA TWA	150 ppm Value 9000 mg/m3 5000 ppm 1000 mg/m3 400 ppm 500 mg/m3 200 ppm	
Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	Type TWA STEL TWA mits (WELs) Type	150 ppm Value 9000 mg/m3 5000 ppm 1000 mg/m3 400 ppm 500 mg/m3 200 ppm Value 27400 mg/m3	
Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) UK. EH40 Workplace Exposure Licomponents Carbon dioxide (CAS	Type TWA STEL TWA mits (WELs) Type STEL	150 ppm Value 9000 mg/m3 5000 ppm 1000 mg/m3 400 ppm 500 mg/m3 200 ppm Value 27400 mg/m3 15000 ppm	
Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) UK. EH40 Workplace Exposure Licomponents Carbon dioxide (CAS	Type TWA STEL TWA mits (WELs) Type	Value 9000 mg/m3 5000 ppm 1000 mg/m3 400 ppm 500 mg/m3 200 ppm Value 27400 mg/m3 15000 ppm 9150 mg/m3	
Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) UK. EH40 Workplace Exposure Licomponents Carbon dioxide (CAS 124-38-9)	Type TWA STEL TWA mits (WELs) Type STEL TWA	Value 9000 mg/m3 5000 ppm 1000 mg/m3 400 ppm 500 mg/m3 200 ppm Value 27400 mg/m3 15000 ppm 9150 mg/m3 5000 ppm	
Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) UK. EH40 Workplace Exposure Licomponents Carbon dioxide (CAS	Type TWA STEL TWA mits (WELs) Type STEL	Value 9000 mg/m3 5000 ppm 1000 mg/m3 400 ppm 500 mg/m3 200 ppm Value 27400 mg/m3 15000 ppm 9150 mg/m3	
Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) UK. EH40 Workplace Exposure Lic Components Carbon dioxide (CAS 124-38-9) Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	Type TWA STEL TWA mits (WELs) Type STEL TWA	Value 9000 mg/m3 5000 ppm 1000 mg/m3 400 ppm 500 mg/m3 200 ppm Value 27400 mg/m3 15000 ppm 9150 mg/m3 5000 ppm	

Components Type Value

400 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU Components Type Value

Carbon dioxide (CAS TWA 9000 mg/m3 124-38-9)

5000 ppm

Biological limit values

Croatia. BLV. Dangerous Substance Exposure Limit Values at Workplace, Annexes 4 (as amended)

Components	Value	Determinant	Specimen	Sampling Time	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	50 mg/l	Acetone	Urine	*	
	50 mg/l	Acetone	Blood	*	
	0,86 umol/l	Acetone	Urine	*	
	0,86 umol/l	Acetone	Blood	*	

^{* -} For sampling details, please see the source document.

Germany, TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling Time
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	25 mg/l	ACETON	Urine	*
	25 mg/l	ACETON	Blood	*

^{* -} For sampling details, please see the source document.

Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices

Components	Value	Determinant	Specimen	Sampling Time
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	25 μg/l	Acetone	Urine	*
	430 µmol/l	Acetone	Urine	*

^{* -} For sampling details, please see the source document.

Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4 Components Value Determinant Specimen Sampling Time

Propan-2-ol; Isopropyl 40 mg/l Acetona Urine alcohol; Isopropanol (CAS

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Determinant	Specimen	Sampling Time	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	25 mg/l	ACETON	Urine	*	
	25 mg/l	ACETON	Blood	*	

^{* -} For sampling details, please see the source document.

Recommended monitoring procedures

67-63-0)

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

General Population

Components	Value	Assessment factor	Notes
Propan-2-ol; Isopropyl alcohol; Isopropanol (C/	AS 67-63-0)		
Long-term, Systemic, Dermal	319 mg/kg bw/day	2	Repeated dose toxicity
Long-term, Systemic, Inhalation	89 mg/m3	2	Repeated dose toxicity
Long-term, Systemic, Oral	26 mg/kg bw/day	2	Repeated dose toxicity

Material name: KONTAKT IPA - Kontakt chemie - Europe

^{* -} For sampling details, please see the source document.

Workers

ComponentsValueAssessment factorNotesPropan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Long-term, Systemic, Dermal888 mg/kg bw/day1Long-term, Systemic, Inhalation500 mg/m31

Predicted no effect concentrations (PNECs)

ComponentsValueAssessment factorNotesPropan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)1Freshwater140,9 mg/l1Secondary poisoning160 mg/kg30OralSediment (freshwater)552 mg/kgSoil28 mg/kg

Exposure guidelines

Cyprus OEL: Skin designation

Propan-2-ol; Isopropyl alcohol; Isopropanol Can be absorbed through the skin.

(CAS 67-63-0)

Hungary OELs: Skin designation

Propan-2-ol; Isopropyl alcohol; Isopropanol Can be absorbed through the skin.

(CAS 67-63-0)

Iceland OELs: Skin designation

Propan-2-ol; Isopropyl alcohol; Isopropanol Can be absorbed through the skin.

(CAS 67-63-0)

Ireland Exposure Limit Values: Skin designation

Propan-2-ol; Isopropyl alcohol; Isopropanol Can be absorbed through the skin.

(CAS 67-63-0)

8.2. Exposure controls

Appropriate engineering

controls applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

Good general ventilation should be used. Ventilation rates should be matched to conditions. If

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

Skin protection

- Hand protection When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough

time of the glove should be longer than the total duration of product use. If work lasts longer than

the breakthrough time, gloves should be changed part-way through. Neoprene gloves are recommended. Suitable gloves can be recommended by the glove supplier.

- Other Not available.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with

organic vapour cartridge and full facepiece. (Filter type A)

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply

with the requirements of environmental protection legislation. Fume scrubbers, filters or

engineering modifications to the process equipment may be necessary to reduce emissions to

acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid.
Form Aerosol.
Colour Colourless.
Odour Alcohol.

Melting point/freezing point -89 °C (-128,2 °F) estimated

Boiling point or initial boiling

point and boiling range

82 °C (179,6 °F)

Flammability (solid, gas) Not available.

Material name: KONTAKT IPA - Kontakt chemie - Europe

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 2 % Explosive limit - upper 12 %

(%)

Flash point 12,0 °C (53,6 °F) Closed cup

Auto-ignition temperature 425 °C (797 °F)

Decomposition temperature Not available.

pH Not applicable.

Solubility(ies)

Solubility (water) Soluble in water

Vapour pressure 43 mbar at 20°C

Vapour density 2,1

Relative density 0,8 at 20°C

Particle characteristics Not available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No relevant additional information available.

9.2.2. Other safety characteristics

Explosive properties Not explosive.

Oxidising properties Not oxidising.

VOC 760 g/l

SECTION 10: Stability and reactivity

10.1. ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid high temperatures.

10.5. Incompatible materials Acids. Strong oxidising agents. Chlorine. Isocyanates.

10.6. Hazardous Carbon oxides.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contactBased on available data, the classification criteria are not met.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components Species Test Results

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Acute Inhalation

LC50 Rat > 25000 mg/m3, 6 h

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitisationBased on available data, the classification criteria are not met.Skin sensitisationBased on available data, the classification criteria are not met.Germ cell mutagenicityBased on available data, the classification criteria are not met.

Material name: KONTAKT IPA - Kontakt chemie - Europe

Carcinogenicity Based on available data, the classification criteria are not met.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Based on available data, the classification criteria are not met. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Not likely, due to the form of the product. **Aspiration hazard**

Mixture versus substance

information

Not available

11.2. Information on other hazards

Endocrine disrupting

properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

Not available. Other information

SECTION 12: Ecological information

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Test Results Components **Species**

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Aquatic

Acute

Crustacea LC50 Brine shrimp (Artemia salina) > 10000 mg/l, 24 hours LC50 Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

> Propan-2-ol; Isopropyl alcohol; Isopropanol 0.05

Not available. **Bioconcentration factor (BCF)** No data available. 12.4. Mobility in soil

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting

properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

12.8. Additional information

Estonia Dangerous substances in soil Data

Propan-2-ol; Isopropyl alcohol; Isopropanol

(CAS 67-63-0)

Chemical pesticides (As the total sum of the active substances)

0,5 mg/kg

Chemical pesticides (As the total sum of the active substances) 20

mg/kg

Chemical pesticides (As the total sum of the active substances) 5 mg/kg

SECTION 13: Disposal considerations

Material name: KONTAKT IPA - Kontakt chemie - Europe

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

The Waste code should be assigned in discussion between the user, the producer and the waste EU waste code

disposal company.

BDS000792AE Version #: 2,0 Revision date: 17-March-2022 Issue date: 19-May-2021

SDS FU

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN1950

14.2. UN proper shipping AEROSOLS, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Hazard No. (ADR) Not available.

Tunnel restriction code D

14.4. Packing group Not available.

14.3. Transport hazard class(es)

ADR/RID - Classification 5F

code:

14.5. Environmental hazards No

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN1950

14.2. UN proper shipping Aerosols, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -

14.4. Packing group Not available.

14.5. Environmental hazards No **ERG Code** 10L

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

14.1. UN number UN1950

14.2. UN proper shipping Aerosols, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -

14.4. Packing group Not available.

14.5. Environmental hazards

Marine pollutant No EmS F-D, S-U

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

14.7. Maritime transport in bulk Not established.

Material name: KONTAKT IPA - Kontakt chemie - Europe

according to IMO instruments

ADR; IATA; IMDG



SDS EU

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Carbon dioxide (CAS 124-38-9)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Other regulations

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as **National regulations**

amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert - Germany).

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value. CEN: European Committee for Standardization.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification,

labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG). MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).

Material name: KONTAKT IPA - Kontakt chemie - Europe SDS FU BDS000792AE Version #: 2,0 Revision date: 17-March-2022 Issue date: 19-May-2021

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).

The classification for health and environmental hazards is derived by a combination of calculation

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value. VOC: Volatile organic compounds.

vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

References

Information on evaluation method leading to the classification of mixture

Full text of any H-statements not written out in full under Sections 2 to 15

methods and test data, if available.

Not available

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Revision information

Product and Company Identification: EU Poison Centre

Composition / Information on Ingredients: Component Summary

SECTION 3: Composition/information on ingredients: Component information SECTION 8: Exposure controls/personal protection: Eye/face protection SECTION 8: Exposure controls/personal protection: Respiratory protection

Physical & Chemical Properties: Multiple Properties

SECTION 12: Ecological information: 12,6. Endocrine disrupting properties

Transport Information: Material Transportation Information

SECTION 16: Other information: Disclaimer

Training information

Disclaimer

Follow training instructions when handling this material.

CRC Industries Europe byba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.