

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 25/05/2023 Revision date: 17/03/2023 Supersedes version of: 15/03/2022 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : KONTAFLON 85

SM3X-48FF-X00X-CSUN UFI

Product code : BDS002519AE Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use Use of the substance/mixture : lubricants

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

CRC Industries Europe B.V. Touwslagerstraat 1

9240 Zele Belgium

T+32(0)52/45.60.11 - F+32(0)52/45.00.34

hse@crcind.com - www.crcind.com

1.4. Emergency telephone number

+32(0)52/45.60.11 **Emergency number**

Office hours: 9-17h CET

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229 Skin corrosion/irritation, Category 2 H315 Serious eye damage/eye irritation, Category 2 H319 Specific target organ toxicity - Single exposure, Category 3, Narcosis H336 H304 Aspiration hazard, Category 1 Hazardous to the aquatic environment - Chronic Hazard, Category 2 H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







GHS02

GHS07

GHS09

Signal word (CLP) : Danger

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Contains : Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane; propan-2-ol; isopropyl

alcohol; isopropanol

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours/spray.

P271 - Use only outdoors or in a well-ventilated area.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 $^{\circ}$ C. P501 - Dispose of contents/container to a hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Other information

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a

concentration equal to or greater than 0,1 %.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	EC-No.: 921-024-6 REACH-no: 01-2119475514- 35	50 – 75	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
butane (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (GB)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691- 32	10 – 25	Flam. Gas 1, H220 Press. Gas (Liq.), H280
propan-2-ol; isopropyl alcohol; isopropanol substance with national workplace exposure limit(s) (GB)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558- 25	1 – 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
tetra-n-butyltitanate	CAS-No.: 5593-70-4 EC-No.: 227-006-8 REACH-no: 01-2119967423- 33	< 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately. Ensure that medical personnel are aware of the material(s)

involved, and take precautions to protect themselves.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop,

get medical attention.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get

medical advice/attention. Seek medical attention if irritation develops.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Seek medical

attention if irritation develops.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately. Rinse mouth. If vomiting occurs, keep

head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

5.3. Advice for firefighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard

firefighting procedures and consider the hazards of other involved materials.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear appropriate protective equipment and clothing during clean-up.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

17/03/2023 (Revision date) GB - en 3/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage

Methods for cleaning up : Mechanically recover the product. For large spills, confine the spill in a dike and charge it

with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to

remove residual contamination.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For disposal of contaminated materials refer to section 13: "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good industrial

hygiene and safety procedures.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this

product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked

up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated

place. Keep cool. Keep container closed when not in use.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

butane (106-97-8)		
United Kingdom - Occupational Exposure Limits		
Local name	Butane	
WEL TWA (OEL TWA) [1]	1450 mg/m³	
WEL TWA (OEL TWA) [2]	600 ppm	
WEL STEL (OEL STEL)	1810 mg/m³	
WEL STEL (OEL STEL) [ppm]	750 ppm	
Remark	Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
United Kingdom - Occupational Exposure Limits	
Local name	Propan-2-ol
WEL TWA (OEL TWA) [1]	999 mg/m³
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	1250 mg/m³
WEL STEL (OEL STEL) [ppm]	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane DNEL/DMEL (Workers) Long-term - systemic effects, dermal 773 mg/kg bodyweight/day Long-term - systemic effects, inhalation 2035 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 699 mg/kg bodyweight/day Long-term - systemic effects, inhalation 608 mg/m³ Long-term - systemic effects, dermal 699 mg/kg bodyweight/day propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 888 mg/kg bodyweight/day Long-term - systemic effects, inhalation 500 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 26 mg/kg bodyweight/day Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, dermal 319 mg/kg bodyweight/day PNEC (Water) PNEC aqua (freshwater) 140.9 mg/l PNEC aqua (marine water) 140.9 mg/l			
Long-term - systemic effects, dermal Long-term - systemic effects, inhalation DNEL/DMEL (General population) Long-term - systemic effects, oral Long-term - systemic effects, inhalation 699 mg/kg bodyweight/day Long-term - systemic effects, inhalation 608 mg/m³ Long-term - systemic effects, dermal 699 mg/kg bodyweight/day propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 888 mg/kg bodyweight/day Long-term - systemic effects, inhalation 500 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 26 mg/kg bodyweight/day Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, dermal 219 mg/kg bodyweight/day PNEC (Water) PNEC aqua (freshwater) 140.9 mg/l PNEC aqua (marine water) 140.9 mg/l	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Long-term - systemic effects, inhalation DNEL/DMEL (General population) Long-term - systemic effects, oral 699 mg/kg bodyweight/day Long-term - systemic effects, inhalation 608 mg/m³ Long-term - systemic effects, dermal 699 mg/kg bodyweight/day propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 888 mg/kg bodyweight/day Long-term - systemic effects, inhalation 500 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 26 mg/kg bodyweight/day Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, dermal 319 mg/kg bodyweight/day PNEC (Water) PNEC aqua (freshwater) 140.9 mg/l PNEC qua (marine water) 140.9 mg/l			
DNEL/DMEL (General population) Long-term - systemic effects, oral 699 mg/kg bodyweight/day Long-term - systemic effects, inhalation 608 mg/m³ Long-term - systemic effects, dermal 699 mg/kg bodyweight/day propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 888 mg/kg bodyweight/day Long-term - systemic effects, inhalation 500 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 26 mg/kg bodyweight/day Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, dermal 319 mg/kg bodyweight/day PNEC (Water) PNEC aqua (freshwater) 140.9 mg/l PNEC aqua (marine water) 140.9 mg/l			
Long-term - systemic effects, inhalation 608 mg/m³ Long-term - systemic effects, inhalation 608 mg/m³ Long-term - systemic effects, dermal 699 mg/kg bodyweight/day propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 888 mg/kg bodyweight/day Long-term - systemic effects, inhalation 500 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 26 mg/kg bodyweight/day Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, dermal 319 mg/kg bodyweight/day PNEC (Water) PNEC aqua (freshwater) 140.9 mg/l PNEC aqua (marine water) 140.9 mg/l			
Long-term - systemic effects, inhalation Long-term - systemic effects, dermal 699 mg/kg bodyweight/day propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) DNEL/DMEL (Workers) Long-term - systemic effects, dermal Long-term - systemic effects, inhalation 500 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 26 mg/kg bodyweight/day Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, dermal 319 mg/kg bodyweight/day PNEC (Water) PNEC aqua (freshwater) 140.9 mg/l PNEC aqua (marine water)			
Long-term - systemic effects, dermal propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) DNEL/DMEL (Workers) Long-term - systemic effects, dermal Long-term - systemic effects, inhalation DNEL/DMEL (General population) Long-term - systemic effects, oral Long-term - systemic effects, inhalation 89 mg/kg bodyweight/day Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, dermal 319 mg/kg bodyweight/day PNEC (Water) PNEC aqua (freshwater) 140.9 mg/l PNEC aqua (marine water) 140.9 mg/l			
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 888 mg/kg bodyweight/day Long-term - systemic effects, inhalation 500 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 26 mg/kg bodyweight/day Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, dermal 319 mg/kg bodyweight/day PNEC (Water) PNEC aqua (freshwater) 140.9 mg/l PNEC aqua (marine water) 140.9 mg/l			
DNEL/DMEL (Workers) Long-term - systemic effects, dermal 888 mg/kg bodyweight/day Long-term - systemic effects, inhalation 500 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 26 mg/kg bodyweight/day Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, dermal 319 mg/kg bodyweight/day PNEC (Water) PNEC aqua (freshwater) 140.9 mg/l PNEC aqua (marine water) 140.9 mg/l			
Long-term - systemic effects, dermal Long-term - systemic effects, inhalation DNEL/DMEL (General population) Long-term - systemic effects, oral Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, dermal 319 mg/kg bodyweight/day PNEC (Water) PNEC aqua (freshwater) 140.9 mg/l PNEC aqua (marine water) 140.9 mg/l			
Long-term - systemic effects, inhalation DNEL/DMEL (General population) Long-term - systemic effects, oral Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, dermal 319 mg/kg bodyweight/day PNEC (Water) PNEC aqua (freshwater) 140.9 mg/l PNEC aqua (marine water) 140.9 mg/l			
DNEL/DMEL (General population) Long-term - systemic effects,oral 26 mg/kg bodyweight/day Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, dermal 319 mg/kg bodyweight/day PNEC (Water) PNEC aqua (freshwater) 140.9 mg/l PNEC aqua (marine water) 140.9 mg/l			
Long-term - systemic effects, oral 26 mg/kg bodyweight/day Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, dermal 319 mg/kg bodyweight/day PNEC (Water) PNEC aqua (freshwater) 140.9 mg/l PNEC aqua (marine water) 140.9 mg/l			
Long-term - systemic effects, inhalation 89 mg/m³ Long-term - systemic effects, dermal 319 mg/kg bodyweight/day PNEC (Water) PNEC aqua (freshwater) 140.9 mg/l PNEC aqua (marine water) 140.9 mg/l			
Long-term - systemic effects, dermal 319 mg/kg bodyweight/day PNEC (Water) PNEC aqua (freshwater) 140.9 mg/l PNEC aqua (marine water) 140.9 mg/l			
PNEC (Water) PNEC aqua (freshwater) 140.9 mg/l PNEC aqua (marine water) 140.9 mg/l			
PNEC aqua (freshwater) 140.9 mg/l PNEC aqua (marine water) 140.9 mg/l			
PNEC aqua (marine water) 140.9 mg/l	PNEC (Water)		
PNEC aqua (intermittent, freshwater) 140.9 mg/l			
PNEC (Sediment)			
PNEC sediment (freshwater) 552 mg/kg dwt			
PNEC sediment (marine water) 552 mg/kg dwt			
PNEC (Soil)			
PNEC soil 28 mg/kg dwt			
PNEC (Oral)			
PNEC oral (secondary poisoning) 160 mg/kg food			

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
PNEC (STP)	
PNEC sewage treatment plant	2251 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):





8.2.2.1. Eye and face protection

Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended.

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: AX

8.2.2.4. Thermal hazards

Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Colourless.

Appearance : Propane/butane propelled liquid.

Odour: Solvent.Odour threshold: Not availableMelting point: Not applicableFreezing point: Not available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Boiling point : Not available

Flammability : Extremely flammable aerosol.

Explosive properties : Pressurised container: May burst if heated.

Explosive limits : Not available
Lower explosion limit : Not available
Upper explosion limit : Not available
Flash point : -35 °C (closed cup)

Auto-ignition temperature > 200 Decomposition temperature : Not available рΗ : Not applicable Viscosity, kinematic $< 10 \text{ mm}^2/\text{s}$ Solubility : insoluble in water. Partition coefficient n-octanol/water (Log Kow) : Not applicable : Not available Vapour pressure Vapour pressure at 50°C Not available Density : 0.705 g/cm3 at 20 °C

Relative density : 0.705 at 20 °C
Relative vapour density at 20 °C : Not available
Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 75 - 100 %

9.2.2. Other safety characteristics

VOC content : 605 g/l

Additional information : For aerosols data for the product without propellant.

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO2).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral): Not classified (Based on available data, the classification criteria are not met)Acute toxicity (dermal): Not classified (Based on available data, the classification criteria are not met)Acute toxicity (inhalation): Not classified (Based on available data, the classification criteria are not met)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C6-C7, n-alkanes, isoa	alkanes, cyclics, <5% n-hexane
LD50 oral rat	5841 mg/kg
LD50 dermal rat	2800 – 3100 mg/kg bodyweight
LC50 Inhalation - Rat	> 25.2 mg/l/4h
propan-2-ol; isopropyl alcohol; isopro	opanol (67-63-0)
LD50 oral rat	5840 mg/kg bodyweight
tetra-n-butyltitanate (5593-70-4)	
LD50 oral rat	3122 mg/kg
LD50 dermal rabbit	5300 mg/kg
LC50 Inhalation - Rat	20100 mg/l
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	pH: Not applicable : Causes serious eye irritation. pH: Not applicable
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness.
Hydrocarbons, C6-C7, n-alkanes, isoa	alkanes, cyclics, <5% n-hexane
STOT-single exposure	May cause drowsiness or dizziness.
propan-2-ol; isopropyl alcohol; isopro	opanol (67-63-0)
STOT-single exposure	May cause drowsiness or dizziness.
tetra-n-butyltitanate (5593-70-4)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure Aspiration hazard	Not classified (Based on available data, the classification criteria are not met)May be fatal if swallowed and enters airways.
KONTAFLON 85	
Vaporizer	Aerosol
Viscosity, kinematic	< 10 mm²/s
Hydrocarbons, C6-C7, n-alkanes, isoa	alkanes, cyclics, <5% n-hexane
Viscosity, kinematic	0.7 mm²/s

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2. Other information

No additional information available

17/03/2023 (Revision date) GB - en 8/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term

(chronic)

long-term : Toxic to aquatic life with long lasting effects.

Not rapidly degradable

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
LC50 - Fish [1]	11.4 mg/l	
EC50 - Crustacea [1]	3 mg/l	
EC50 72h - Algae [1]	10 mg/l	
LOEC (chronic)	0.32 mg/l	
NOEC (chronic)	0.17 mg/l	
NOEC chronic fish	2.04 mg/l	
NOEC chronic crustacea	1 mg/l	
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)		
LC50 - Fish [1]	10000 mg/l	
LC50 - Fish [2]	9640 mg/l	
tetra-n-butyltitanate (5593-70-4)		
LC50 - Fish [1]	1825 mg/l	
EC50 - Crustacea [1]	1300 mg/l Daphnia magna (Water flea)	
EC50 72h - Algae [1]	225 mg/l	

12.2. Persistence and degradability

KONTAFLON 85	
Persistence and degradability	Not established. No data is available on the degradability of this product.

12.3. Bioaccumulative potential

KONTAFLON 85	
Partition coefficient n-octanol/water (Log Kow) Not applicable	
tetra-n-butyltitanate (5593-70-4)	
Partition coefficient n-octanol/water (Log Pow)	0.84

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

KONTAFLON 85	
Results of PBT assessment	Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

Additional information : No other effects known

Global warming potential (GWP) : 1 (Fluorinated greenhouse gases - (EC) No 517/2014)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods European List of Waste (LoW) code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	umber			
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shippin	g name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document descr	iption			
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1 ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard o	class(es)			
2.1	2.1	2.1	2.1	2.1
22	2	2	2	**************************************
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information	on available			

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR): MP9Transport category (ADR): 2Special provisions for carriage - Packages (ADR): V14Special provisions for carriage - Loading, unloading: CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2 Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

: SG69

Limited quantities (IMDG) SP277 Excepted quantities (IMDG) : E0 Packing instructions (IMDG) : P207, LP200 Special packing provisions (IMDG) : PP87, L2 : F-D EmS-No. (Fire) : S-U EmS-No. (Spillage) Stowage category (IMDG) : None Stowage and handling (IMDG) : SW1, SW22

Air transport

Segregation (IMDG)

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L

Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200

Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Mixed packing provisions (RID) : MP9

Transport category (RID) : 2

Special provisions for carriage – Packages (RID) : W14

Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2
Hazard identification number (RID) : 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 605 g/l

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:		
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disrupting properties	

Full text of H- and EUH-statements:		
Aerosol 1	Aerosol, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Gas 1	Flammable gases, Category 1	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H280	Contains gas under pressure; may explode if heated.	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H411	Toxic to aquatic life with long lasting effects.	
Press. Gas (Liq.)	Gases under pressure : Liquefied gas	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.