



SAFETY DATA SHEET

Version #: 01 Issue date: 08-March-2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture TUNER 600

Registration number -

UFI:

Austria: 9F3X-482P-A00Y-13PH
Belgium: 9F3X-482P-A00Y-13PH
Bulgaria: 9F3X-482P-A00Y-13PH
Croatia: 9F3X-482P-A00Y-13PH
Cyprus: 9F3X-482P-A00Y-13PH
Czech Republic: 9F3X-482P-A00Y-13PH
Denmark: 9F3X-482P-A00Y-13PH
Estonia: 9F3X-482P-A00Y-13PH
EU: 9F3X-482P-A00Y-13PH
Finland: 9F3X-482P-A00Y-13PH
France: 9F3X-482P-A00Y-13PH
Germany: 9F3X-482P-A00Y-13PH
Great Britain: 9F3X-482P-A00Y-13PH
Greece: 9F3X-482P-A00Y-13PH
Hungary: 9F3X-482P-A00Y-13PH
Iceland: 9F3X-482P-A00Y-13PH
Italy: 9F3X-482P-A00Y-13PH
Latvia: 9F3X-482P-A00Y-13PH
Lithuania: 9F3X-482P-A00Y-13PH
Luxembourg: 9F3X-482P-A00Y-13PH
Malta: 9F3X-482P-A00Y-13PH
Netherlands: 9F3X-482P-A00Y-13PH
Norway: 9F3X-482P-A00Y-13PH
Poland: 9F3X-482P-A00Y-13PH
Portugal: 9F3X-482P-A00Y-13PH
Romania: 9F3X-482P-A00Y-13PH
Slovakia: 9F3X-482P-A00Y-13PH
Slovenia: 9F3X-482P-A00Y-13PH
Spain: 9F3X-482P-A00Y-13PH
Sweden: 9F3X-482P-A00Y-13PH

Synonyms None.

Product code BDS000269AE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaners - Precision

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company name CRC Industries Europe bv

Address Touwslagerstraat 1
9240 Zele
Belgium

Telephone +32(0)52/45.60.11

Fax +32(0)52/45.00.34

E-mail hse@crcind.com

Website www.crcind.com

1.4. Emergency telephone number Tel.: +32(0)52/45.60.11 (office hours: 9-17h CET)

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Austria National Poisons Information Centre +431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Belgium National Poisons Control Center 070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Bulgaria National Toxicological Information Centre	+359 2 9154233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Czech Republic National Poisons Information Centre	+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Denmark National Poisons Control Center	+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Estonia National Poisons Information Centre	16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)
Finland National Poison Information Center	(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
France National Poisons Control Center	ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Hungary National Emergency Phone Number	36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Lithuania Neatidėliotina informacija apsinuodijus	+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Malta Accident and Emergency Department	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Netherlands National Poisons Information Center (NVIC)	030-274 88 88 (Only for the purpose of informing medical personnel in cases of acute intoxications)
Norway Norwegian Poison Information Center	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Portugal Poison Centre	800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Romania Număr de telefon care poate fi apelat în caz de urgență:	021 5992300, int. 291 Spitalul Clinic de Urgență București: spital@urgentaflorasca.ro
Romania	0265 212111, 0265 211292, 0265 217235 Spitalul Clinic Județean de Urgență Târgu Mureș: secretariat@spitjudms.ro
Slovakia National Toxicological Information Centre	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Sweden National Poison Information Center	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Switzerland Tox Info Suisse	145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
----------	------------	---

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 2	H411 - Toxic to aquatic life with long lasting effects.
--	------------	---

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended**Contains:** hydrocarbons,C6,isoalkanes,< 5% n-hexane, Pentane**Hazard pictograms****Signal word** Danger**Hazard statements**

H222 Extremely flammable aerosol.
 H229 Pressurized container: May burst if heated.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements**Prevention**

P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing mist/vapours.
 P271 Use only outdoors or in a well-ventilated area.

Response Not assigned.**Storage**

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information Regulation (EC) No 648/2004 on detergents: aliphatic hydrocarbons > 30 %**2.3. Other hazards**

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
hydrocarbons,C6,isoalkanes,< 5% n-hexane	25 - 50	EC931-254-9 931-254-9	01-2119484651-34	649-328-00-1	
Classification: Flam. Liq. 2;H225, Skin Irrit. 2;H315, STOT SE 3;H336, Asp. Tox. 1;H304, Aquatic Chronic 2;H411					
Pentane	25 - 50	109-66-0 203-692-4	01-2119459286-30	601-006-00-1	#
Classification: Flam. Liq. 2;H225, STOT SE 3;H336, Asp. Tox. 1;H304, Aquatic Chronic 2;H411					
Carbon dioxide	5 - 10	124-38-9 204-696-9	-	-	#
Classification: Press. Gas;H280					

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).
 M: M-factor
 PBT: persistent, bioaccumulative and toxic substance.
 vPvB: very persistent and very bioaccumulative substance.
 All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.**SECTION 4: First aid measures****General information**

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures**Inhalation**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.

Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.
4.2. Most important symptoms and effects, both acute and delayed	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards	Extremely flammable aerosol.
5.1. Extinguishing media	
Suitable extinguishing media	Foam. Powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Special fire fighting procedures	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.
For emergency responders	Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
6.2. Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)
7.3. Specific end use(s)	Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria

Components	Type	Value
hydrocarbons, C6, isoalkanes, < 5% n-hexane	TWA (MAK)	200 ppm

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	Ceiling	18000 mg/m ³
	MAK	10000 ppm 9000 mg/m ³ 5000 ppm
Pentane (CAS 109-66-0)	Ceiling	3600 mg/m ³ 1200 ppm
	MAK	1800 mg/m ³ 600 ppm

Belgium. Exposure Limit Values

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	54784 mg/m ³ 30000 ppm
	TWA	9131 mg/m ³ 5000 ppm
Pentane (CAS 109-66-0)	STEL	2250 mg/m ³ 750 ppm
	TWA	1800 mg/m ³ 600 ppm

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³ 5000 ppm
		3000 mg/m ³ 1000 ppm

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	MAC	9000 mg/m ³ 5000 ppm
		3000 mg/m ³ 1000 ppm

Czech Republic. OELs. Government Decree 361

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	Ceiling	45000 mg/m ³
	TWA	9000 mg/m ³
Pentane (CAS 109-66-0)	Ceiling	4500 mg/m ³
	TWA	3000 mg/m ³

Denmark. Exposure Limit Values

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m3
		5000 ppm
Pentane (CAS 109-66-0)	TLV	1500 mg/m3
		500 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m3
		1000 ppm

Finland

Components	Type	Value
hydrocarbons,C6,isoalkanes,< 5% n-hexane	TWA	500 mg/m3

Finland. Workplace Exposure Limits

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m3
		5000 ppm
Pentane (CAS 109-66-0)	STEL	1900 mg/m3
		630 ppm
	TWA	1500 mg/m3
		500 ppm

France

Components	Type	Value
hydrocarbons,C6,isoalkanes,< 5% n-hexane	STEL	1500 mg/m3
	TWA	1000 mg/m3

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	VME	9000 mg/m3
		5000 ppm
Pentane (CAS 109-66-0)	VME	3000 mg/m3
		1000 ppm
	Regulatory status: Regulatory binding (VRC)	

Germany

Components	Type	Value
hydrocarbons,C6,isoalkanes,< 5% n-hexane	MAK	3000 mg/m3

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m3
		5000 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m3
		1000 ppm

Germany - TRGS 900

Components	Type	Value
hydrocarbons,C6,isoalkanes,< 5% n-hexane	TWA	1500 mg/m3

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	AGW	9100 mg/m3 5000 ppm
Pentane (CAS 109-66-0)	AGW	3000 mg/m3 1000 ppm

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3 5000 ppm
	TWA	9000 mg/m3 5000 ppm
Pentane (CAS 109-66-0)	STEL	2950 mg/m3 1000 ppm
	TWA	2950 mg/m3 1000 ppm

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
Pentane (CAS 109-66-0)	TWA	2950 mg/m3

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3 5000 ppm
Pentane (CAS 109-66-0)	TWA	1500 mg/m3 500 ppm

Ireland. Occupational Exposure Limits

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3 5000 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m3 1000 ppm

Italy. Occupational Exposure Limits

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3 5000 ppm
Pentane (CAS 109-66-0)	TWA	2000 mg/m3 667 ppm

Latvia

Components	Type	Value
hydrocarbons,C6,isoalkanes,< 5% n-hexane	STEL	300 mg/m3
	TWA (AER)	100 mg/m3

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value	
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³	
		5000 ppm	
Pentane (CAS 109-66-0)	STEL	300 mg/m ³	
		TWA	3000 mg/m ³
			1000 ppm

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³
		5000 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m ³
		1000 ppm

Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³
		5000 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m ³
		1000 ppm

Netherlands. OELs (binding)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³
		1800 mg/m ³
Pentane (CAS 109-66-0)	TWA	1800 mg/m ³
		250 ppm

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m ³
		5000 ppm
Pentane (CAS 109-66-0)	TLV	750 mg/m ³
		250 ppm

Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	27000 mg/m ³
		0 ppm
	TWA	9000 mg/m ³
		0 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m ³
		0 ppm

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³
		5000 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m ³
		1000 ppm

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
Pentane (CAS 109-66-0)	TWA	1000 ppm

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m3
		1000 ppm

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m3
		1000 ppm

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m3
		1000 ppm

Spain. Occupational Exposure Limits

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9150 mg/m3
		5000 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m3
		1000 ppm

Sweden

Components	Type	Value
hydrocarbons,C6,isoalkanes,< 5% n-hexane	STEL (STV)	300 ppm
	TWA	200 ppm

Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	18000 mg/m3
		10000 ppm
	TWA	9000 mg/m3
Pentane (CAS 109-66-0)	STEL	5000 ppm
		2000 mg/m3
	TWA	750 ppm
		1800 mg/m3
		600 ppm

Switzerland Components	Type	Value
hydrocarbons,C6,isoalkanes, s,< 5% n-hexane	TWA	500 ppm
Switzerland. SUVA Grenzwerte am Arbeitsplatz Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3 5000 ppm
Pentane (CAS 109-66-0)	STEL	3600 mg/m3 1200 ppm
	TWA	1800 mg/m3 600 ppm
UK. EH40 Workplace Exposure Limits (WELs) Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	27400 mg/m3 15000 ppm
	TWA	9150 mg/m3 5000 ppm
Pentane (CAS 109-66-0)	TWA	1800 mg/m3 600 ppm
EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3 5000 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m3 1000 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs)

General Population

Components	Value	Assessment factor	Notes
hydrocarbons,C6,isoalkanes,< 5% n-hexane (CAS EC931-254-9)			
Long-term, Systemic, Dermal	1377 mg/kg bw/day		
Long-term, Systemic, Inhalation	1131 mg/kg bw/day		
Long-term, Systemic, Oral	1301 mg/kg bw/day		
Pentane (CAS 109-66-0)			
Long-term, Systemic, Dermal	214 mg/kg bw/day	5	Repeated dose toxicity
Long-term, Systemic, Inhalation	643 mg/m3	5	Repeated dose toxicity

Workers

Components	Value	Assessment factor	Notes
hydrocarbons,C6,isoalkanes,< 5% n-hexane (CAS EC931-254-9)			
Long-term, Systemic, Dermal	13964 mg/kg bw/day		
Long-term, Systemic, Inhalation	5306 mg/m3		
Pentane (CAS 109-66-0)			
Long-term, Systemic, Dermal	432 mg/kg bw/day	3	Repeated dose toxicity
Long-term, Systemic, Inhalation	3000 mg/m3	3	Repeated dose toxicity

Predicted no effect concentrations (PNECs)

Components	Value	Assessment factor	Notes
Pentane (CAS 109-66-0)			
Freshwater	230 µg/l	1	
Sediment (freshwater)	1,2 mg/kg	1	
Soil	0,55 mg/kg	1	

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection

Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

Skin protection

- Hand protection

When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Full contact: Glove material: nitrile. Use gloves with breakthrough time of 30 minutes. Minimum glove thickness 0.38 mm.

- Other

Wear appropriate chemical resistant clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge and full facepiece. (Filter type AX)

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

Hygiene measures

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Aerosol.
Colour	Colourless.
Odour	Solvent.
Melting point/freezing point	-129,7 °C (-201,5 °F) estimated
Boiling point or initial boiling point and boiling range	> 40 °C (> 104 °F)
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	1 % estimated
Explosive limit – upper (%)	7,8 % estimated
Flash point	< 0 °C (< 32,0 °F) Closed cup
Auto-ignition temperature	> 200 °C (> 392 °F)
Decomposition temperature	Not available.
pH	Not applicable.
Solubility(ies)	
Solubility (water)	Insoluble in water
Vapour pressure	3567,5 hPa estimated
Vapour density	> 1
Vapour density temp.	20 °C (68 °F)
Relative density	0,65 g/cm ³ at 20°C
Particle characteristics	Not available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes No relevant additional information available.

9.2.2. Other safety characteristics

Evaporation rate 1 (Ether=1)

Explosive properties	Not explosive.
Heat of combustion	19,78 kJ/g estimated
Oxidising properties	Not oxidising.
VOC	620 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid high temperatures.
10.5. Incompatible materials	Strong oxidising agents. Aluminium.
10.6. Hazardous decomposition products	Carbon oxides.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

11.1. Information on toxicological effects

Acute toxicity Classification based on calculation method. Based on available data, the classification criteria are not met.

Product	Species	Test Results
TUNER 600		
Acute		
Oral		
LD50	Rat	4079 mg/kg
Components		
hydrocarbons,C6,isoalkanes,< 5% n-hexane		
Acute		
Dermal		
LD50	Rabbit	3350 mg/kg, 4 h
Inhalation		
LD50	Rat	259354 mg/m3
Oral		
LD50	Rat	16750 mg/kg
Pentane (CAS 109-66-0)		
Acute		
Dermal		
LD50	Rabbit	> 3000 mg/kg
Inhalation		
LC50	Rat	364 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory sensitisation	Based on available data, the classification criteria are not met.	
Skin sensitisation	Based on available data, the classification criteria are not met.	

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicity Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Not likely, due to the form of the product.

Mixture versus substance information Not available.

11.2. Information on other hazards

Endocrine disrupting properties The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life with long lasting effects.

Components		Species	Test Results
hydrocarbons,C6,isoalkanes,< 5% n-hexane			
<i>Acute</i>			
Other	EC50	Pseudokirchnerella subcapitata	13,6 mg/l, 72 hours
	NOEC	Pseudokirchnerella subcapitata	3 mg/l, 72 hours
<i>Aquatic</i>			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	31,9 mg/l, 48 hours
	NOEC	Daphnia magna	7,14 mg/l, 21 days
Fish	EC50	Rainbow trout	18,3 mg/l, 96 hours
	NOEC	Rainbow trout	4,09 mg/l, 28 days

12.2. Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

Pentane 3,39

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB assessment This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting properties The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.
GWP: 2

Substance Global Warming Potential per (Annex IV), Regulation 517/2014/EU on fluorinated greenhouse gases, as amended

Pentane (CAS 109-66-0) 5

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1950
14.2. UN proper shipping name	AEROSOLS, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Hazard No. (ADR)	Not available.
Tunnel restriction code	D
14.4. Packing group	Not available.
14.3. Transport hazard class(es)	
ADR/RID - Classification code:	5F
14.5. Environmental hazards	Yes
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
14.4. Packing group	Not available.
14.5. Environmental hazards	Yes
ERG Code	10L
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.


IMDG

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable, MARINE POLLUTANT
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
14.4. Packing group	Not available.
14.5. Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
14.7. Maritime transport in bulk according to IMO instruments	Not established.

ADR; IATA; IMDG



Marine pollutant



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Carbon dioxide (CAS 124-38-9)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Pentane (CAS 109-66-0)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).
ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).
CAS: Chemical Abstract Service.
Ceiling: Short Term Exposure Limit Ceiling value.
CEN: European Committee for Standardization.
CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.
GWP: Global Warming Potential.
IATA: International Air Transport Association.
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
IMDG: International Maritime Dangerous Goods.
MAC: Maximum Allowed Concentration.
MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).
MARPOL: International Convention for the Prevention of Pollution from Ships.
PBT: Persistent, bioaccumulative and toxic.
REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation, Authorization and Restriction of Chemicals).
RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
STEL: Short term exposure limit.
TLV: Threshold Limit Value.
TWA: Time Weighted Average.
VLE: Exposure Limit Value.
VME: Exposure Average Value.
VOC: Volatile organic compounds.
vPvB: Very persistent and very bioaccumulative.
STEL: Short-term Exposure Limit.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Revision information

None.

Training information

Follow training instructions when handling this material.

Disclaimer

CRC Industries Europe bvba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.