



Data sheet: DC-230



Product code	DC-230
Product name	Network Storage Router
EAN code	8716502010196
Qty. masterpack/carton	5/20
Giftbox weight	1296 gr.
Giftbox dimension	260 (W) x 85 (D) x 190 (H)

This Broadband Router enables you to share your existing broadband Internet connection effortlessly among a number of PCs via a single subscription. Thanks to the integrated switch, you can directly connect 4 PCs, which then all have the possibility of access to the Internet. The built-in Firewall ensures that this Internet entrance is safeguarded against intruders. With the two USB ports it is easy to share two external USB hard disks and/or flash disks with all the other PC's in your network. The connected storage devices can easily be accessed via the internet from any location in the world.

Box content:

- Network Storage Router
- CD Rom, Power Adapter
- User manual
- Wall mounting bracket
- UTP Cable

System requirements:

- Windows 2000/XP
- (Wireless) Network adapter
- Adsl or Cable Modem

IP Sharing

The NAT/NAPT function lets you share the ADSL line to all the Intranet users (support up to 253 users). It also provides virtual server and virtual DMZ functions to let your internal servers be accessed from the Internet.

Support Network-Attached Storage

NAS supported following protocols: Windows File Sharing, FTP File Sharing, HTTP File Sharing(WebDAV-http upload), APPLE File Sharing.



INTERNET



NETWORK



CONNECTIVITY



ENTERTAINMENT



EXPANDING POSSIBILITIES



NETWORK

Support Peer-to-Peer and Server-Based Printing

Supports both Peer-to-Peer and Server-based printing. LAN clients can connect directly with the print server to execute printing jobs (Peer-to-Peer printing); or clients can send print jobs first to a server (queuing jobs) and allow the server to connect with the print server to execute the printing jobs (Server-based printing).

Provide Complete Printing Methods

The print server provides LPR, IPP, SMB/TCP, Raw Printing and Unix Logical Printer printing methods. You can choose the best printing method according to your environment.

Web Configuration

You can configure the router through the friendly Web user interface with a browser.

Features:

- NAT/NAPT IP Sharing
- Anti-DoS Firewall
- Virtual Server/DMZ
- Provides two USB 2.0 port to connect to printer and USB storage.
- Windows File Sharing, FTP File Sharing, HTTP File Sharing(WebDAV-http upload), APPLE File Sharing.
- User/Group based Permission Control and Folder Based Permission Control.
- Obtain WAN IP by PPPoE/Static IP/PPTP/DHCP
- DHCP Server
- Web User Interface (Remote Configuration)
- System Status
- Security Log
- Firmware Upgrade

Specification:

- Product DC-230
- CPU RDC 3210
- Switch Realtek RTL8305SC (5 Port Switch)
- Flash 4 MB NOR Flash
- RAM 32 MB SDRAM
- WAN Port 10/100M UTP Port x 1
- LAN Ports 10/100M UTP Port x 4
- Power 12V DC, 1A Linear Power Adaptor
- Dimension 30(H)*187(W)*100(D) mm
- Temperature 10~40 °C
- Humidity 10~90% (Non-Condensing)
- Certification FCC Class B, CE Mark, C-Tick

P. 2-2.



INTERNET



NETWORK



CONNECTIVITY



ENTERTAINMENT



EXPANDING POSSIBILITIES